

# SPECIFICATION

1. **PRODUCT:**  
4 Gang Surge Protected 13A non-rewireable extension socket with neon  
with 2M Cable

Model No. : 9988NS-2M

2. **CURRENT RATING:**  
13A 250 V a.c.

3. **CONSTRUCTION:**

ITEM	DESCRIPTION	MATERIAL
1	Socket base and cover	FRPP
2	Socket Terminals (Bus bar)	Brass
3	Cover Screw	Mild steel nickel plated
4	Shutter	Nylon (PA)
5	Spring	Mild steel
6	Neon lamp with 220k $\Omega$ resistor	Orange light
7	Neon lamp cover	Polycarbonate (PC)
8	Surge component	Metal Oxide Varistor
9	Plug	13A BS 1363 plug
10	Cable	PVC, BS6500 3X1.25mm <sup>2</sup>

4. **APPROVAL:**

MOV: VDE approved (varistor)  
PLUG: BSI Kitemark licence KM54406

5. **STANDARD:**  
BS 1363/A, BS 5733

6. **SURGE PROTECTION DATA**

Voltage : 220V – 240V  
Operating Voltage (Vac rms) : 300V Max.  
Mains Three Way Protection : LN LE NE  
Peak Current (A) : 4.5kA

Max. Energy (Joules) : 3 x 125J  
Max. Clamping Voltage : 775Volts  
Response Time (nS) : <50ns

7. **PRODUCT PHOTO**



**8. CONDITIONS OF USE**

- a) an ambient temperature in the range  $-5^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ , the average value over 24 hours not exceeding  $25^{\circ}\text{C}$ .
- b) a situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperatures above the limits specified in a);
- c) an altitude not exceeding 2000 metres above sea level;
- d) an atmosphere no subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions.

**9. SAFETY SPECIFICATIONS**

NO.	ITEM	CONDITIONS	REQUIREMENTS
1	Appearance		No defect such as cracks, deep scratches or blemishes
2	Marking		Shall be legible and must be clear
3	Insulation Resistance	500 + 250 V d.c. 1 min	Shall not be less than 5 M $\Omega$
4	Dielectric strength	250 +/- 60 V 1 min	No damage or breakdown
5	Resistance to aging	70 $^{\circ}$ +/- 5 $^{\circ}$ 168 hrs	No cracks or become sticky
6	Construction	20 $^{\circ}$ +/- 5 $^{\circ}$	Complied with Figure 11,12,14, 16 gauge
7.	Torque test	Value of 0.6N.m. (6.1 kgf/cm)	Terminal, cord grip and cover screws shall withstand the torque applied
8	Glow Wire Test	650 $^{\circ}$ /750 $^{\circ}$ electrically heated	Flame must extinguish within 30 seconds.
9	Temperature rise	14 A 250 V	Temperature rise must not exceed: 1. Terminals or terminations : 52K 2. Accessible surface: 52K
10	Drop Test	Fit with 3G1.25mm <sup>2</sup> cable, 2.25 m and drop at a height of 0.4m above the floor .	No external damage which might affect safety and no components shall have become detached.
11	Live parts accessibility	subjected to 1.0 mm test probe with applied force of 5N when they are mounted and wired as in normal use.	Live parts of socket shall not be accessible.

**10. TEST REPORT/CERTIFICATE**

Socket: ET-R0718679 & ET-R0626403(S1) issued by Intertek Testing Services

Plug: KM54406 issued by BSI

Cable: 243/4569447 issued by BSI