

Wiha Flag Handle and Offset Screwdriver.

TORX® Driver.



370 TORX® driver with flag handle.


Blade: Chrome-vanadium steel, through hardened, black finish.

Handle: Wiha flag handle.

Application: For high torque transfer with small screws, especially when

replacing indexable inserts on milling heads.

Order-No.		=	01		=		
03724 6	T5	35	2.0	19.0	67	10	
03725 3	T6	35	2.0	19.0	67	10	
03726 0	T7	35	2.5	19.0	67	10	
03727 7	T8	40	2.5	19.0	72	10	
03728 4	T9	40	3.0	23.5	74	10 (** 5.61)	
03729 1	T10	40	3.0	23.5	74	10	
03730 7	T15	45	3.5	28.0	80	10	
03731 4	T20	45	4.0	28.0	80	10	



370 VB TORX® driver set with flag handle.

Black finish, in small bench stand, 7-pcs.

Small, stable metal bench stand to stand tip symbols

printed to scale.

Extra:

Order-No.						_
25625 8	Bench	stand equ	1 1			
	370	T6x35	T7x35	T8x40	T9x40	
		T10x40	T15x45	T20x45		

Offset Screwdriver.



207 Slotted offset screwdriver.

With handle.

Blade: Chrome-vanadium steel, through hardened, chrome plated.

Standards: Produced according to DIN 5200.

Application: To work in tight work spaces.

3.5 4.0	0.6	90	8.5	3.5	10	831-074
	0.8	100	0.0000000000000000000000000000000000000			U -
		100	9.0	4.0	10	103-791
5.5	1.0	125	10.5	5.5	10	831-086
6.5•	1.2	125	13.5	6.5	10	108-702
8.0	1.2	150	17.0	8.0	10	103-703
0.0	1.6	175	24.0	9.0	10	
2.0	2.0	200	27.0	10.0	5	
N 100001	8.0 0.0 2.0	8.0 1.2 0.0 1.6 2.0 2.0	8.0 1.2 150 0.0 1.6 175 2.0 2.0 200	8.0 1.2 150 17.0 0.0 1.6 175 24.0	8.0 1.2 150 17.0 8.0 0.0 1.6 175 24.0 9.0 2.0 2.0 200 27.0 10.0	8.0 1.2 150 17.0 8.0 10 0.0 1.6 175 24.0 9.0 10 2.0 2.0 200 27.0 10.0 5





61 Phillips offset screwdriver.

With handle.

Blade: Chrome-vanadium steel, through hardened, chrome plated.

Standards: Produced according to DIN 5208.

Application: To work in tight work spaces.

Order-No.	+ +	=	-	01		
00144 5	PH 1 + 2	125	14.5	5.5	10	831-153
00145 2	PH 2 + 3	150	21.0	8.0	10	231-165
00146 9	PH 3 + 4	200	25.0	10.0	10	03







Pozidriv offset screwdriver.
With handle.

Blade: Chrome-vanadium steel, through hardened, black finish.

Standards: Produced according to DIN 5208.

Application: To work in tight work spaces.

Order-No.	• •	=	~	•1		
00432 3	PZ 1 + 2	125	14.5	5.5	10	831-219
00433 0	PZ 2 + 3	150	21.0	8.0		831-220
00434 7	PZ 3 + 4				10	