

# 3664132 - 1377074-1

## Micro-MaTch Miniature Connector System

PCB + EIA-tape

Printed Circuit Board (PCB) and Micro-Match SMD packed in EIA – tape

Flatcables

215079 - Female-on-Board Connector	Top Entry
215460 - Female-on-Board Connector	Side Entry
188275 - Female-on-Board Connector	Surface Mount Device (S.M.D)
215464 - Male-on-Board Connector	
215083 - Male-on-Wire Connector	
215570 - Paddle Board Connector	
COSI - Crimp On Snap IN Connector	

Specials - <u>Locking Latch</u>	<u>SMC Connector</u>	<u>Male SMD</u>	<u>In-board SMD</u>
338068	100411	338728	188431
338069			
338070			

## Technical Features

Centerline	1.27mm (staggered)
Number of Positions	4,6,8,10,12,14,16,18 and 20
Housing Material	red glassfilled polyester for flammability rating UL94-V-0
Wire Range	solid 0.3mm Ø Stranded 0.08mm <sup>2</sup> (AWG 28) 7 strands Insulation Ø 0.9 mm
Temperature Range	-40 C to + 105C
PC Board Thickness	1.6mm
AMP Product Spec	108 – 19052
Application Specification	114 – 19016 male-on wire/paddle board connector 114 19027 female smc connector