



**Led Signalleuchten Einbaudurchmesser 8 mm**  
**Led Indicaators Body diameter 8 mm**

**Blinkend mit Außenreflektor**  
**Flashing Led with exterior reflector**

Bestell-Nr. Part No.	Farbe Colour	V <sub>OP</sub> +10% (V)	I <sub>OP</sub> max. (mA)	V <sub>F</sub> (V)	I <sub>V</sub> typ. (mcd) *I <sub>F</sub> = 20mA	I <sub>F</sub> max. (mA)	Abb. Illu.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	
1906*000	Rot Red	3,5-13	38-56	9	nicht meßbar not measurable	56	A	19040-A	A
1906*001	Grün Green	3,5-13	38-56	9		56	A		
1906*002	Gelb Yellow	3,5-13	38-56	9		56	A		
1906*003	S. rot S. red	3,5-13	38-56	9		56	A		
1906*050	Rot Red	3,5-13	38-56	9		56	C		
1906*051	Grün Green	3,5-13	38-56	9		56	C		
1906*052	Gelb Yellow	3,5-13	38-56	9		56	C		
1906*053	S. rot S. red	3,5-13	38-56	9		56	C		
1906*350	Rot Red	24	20-35				B	19040-B	B
1906*351	Grün Green	24	20-35				B		
1906*352	Gelb Yellow	24	20-35				B		
1906*353	S. rot S. red	24	20-35				B		
								19060050 - 19060053, wird als verkürzte Ausführung mit Steckkontakten geliefert, <b>siehe Zeichnung Nr. 19040-C</b> 19060050 - 19060053, short version with tabs, <b>see drawing no. 19040-C</b>	C



Arbeitstemperatur (T<sub>OP</sub>): -55°C - +70°C  
 Lagertemperatur (T<sub>STG</sub>): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0      Schwarzchrom = 1  
 Beispiel:              19060000 rot mit Glanzchrom  
                              19061000 rot mit Schwarzchrom

Blinkfrequenz:              (2,5 - 1,5 Hz./Cyc.)  
                                      abhängig von angelegter Spannung

**Led Signalleuchten mit anderen Spannungen auf Anfrage**

Technische Änderungen vorbehalten

Operating temperature (T<sub>OP</sub>): -55°C - +70°C  
 Storage temperature (T<sub>STG</sub>): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0      Black chrome = 1  
 Example:                      19060000 red with bright chrome  
                                      19061000 red with black chrome

Flashing frequency:              (2,5 - 1,5 Hz./Cyc.)  
                                      depending on supply voltage

**Led Indicators with other voltages upon request**

Specification subject to change without notice