

TYPE: MC 100-000

Programmable Terminal Block

Part number assembly

76

**Features**

Cable strain	Stress on points
Conduct	Respective terminal for ground, 0 or
Insulating body	High-temperature PVC or
Series	MC 100 series for ground
Color	Green

Specifications

Operating temperature	-55 to +100 °C
Storage temperature	up to +150 °C, down to

Dimensions

Cable rating	1 cable, MC 1000
Maximum cable length and	40 meters, max
Maximum resistance	~0.0001 Ω/100m
Wire cross-section	0.5-2.5 mm ²
Wire length	1.2 m, max

Accessories**MC 1000 Series MC 1000**

Green Series - 4 Channels

**Block Dimensions (mm)**

Part No.	Pin(s)	Height	Length
MC 1000 0000	1	25.00	100.00
MC 1000 0001	2	25.00	100.00
MC 1000 0002	3	25.00	100.00
MC 1000 0003	4	25.00	100.00
MC 1000 0004	5	25.00	100.00
MC 1000 0005	6	25.00	100.00
MC 1000 0006	7	25.00	100.00
MC 1000 0007	8	25.00	100.00
MC 1000 0008	9	25.00	100.00
MC 1000 0009	10	25.00	100.00
MC 1000 0010	11	25.00	100.00
MC 1000 0011	12	25.00	100.00
MC 1000 0012	13	25.00	100.00
MC 1000 0013	14	25.00	100.00