

AQT Compact Balances



“The Affordable Choice”

AQT Compact Balances

“The Affordable Choice”

The AQT is an economically priced balance tailored for many weighing applications.

- Robust case design
- Large stainless steel weighing pan
- Low battery indicator
- Clear LCD display with backlight
- Auto power off to save battery life
- Battery or mains adapter (adapter supplied as standard)
- Various weighing units available
- Windshield as standard on all models
- Integral security bracket
- Spirit level
- Height adjustable feet

SPECIFICATIONS

| Model | AQT 200 | AQT 250 | AQT 600 | AQT 1500 | AQT 2000 | AQT 5000 |
|----------------------------|--|---------|---------|----------|----------|----------|
| Maximum capacity | 200g | 250g | 600g | 1500g | 2000g | 5000g |
| Readability | 0.01g | 0.1g | 0.1g | 0.1g | 1g | 1g |
| Resolution | 1:20000 | 1:2500 | 1:6000 | 1:15000 | 1:2000 | 1:5000 |
| Repeatability | 0.02g | 0.1g | 0.1g | 0.2g | 1g | 1g |
| Linearity (±) | 0.02g | 0.1g | 0.1g | 0.2g | 1g | 1g |
| Typical stabilisation time | 3 secs | 2 secs | 2 secs | 3 secs | 2 secs | 2 secs |
| Units of measure | AQT 200: g,ct,oz,dwt,Taels (3) - Singapore, Hong Kong, Taiwan AQT 250 and 600: g, ct, oz, dwt AQT 1500, 2000 and 5000: kg,g,lb,oz | | | | | |
| Operating temperature | 0°C to 40°C / 32°F to 104°F | | | | | |
| Power supply | 12VAC @ 150mA adapter or 6 xAA batteries | | | | | |
| Calibration | Push button using external mass | | | | | |
| Display | 6 digit LCD, 15mm digits with backlight | | | | | |
| Draught shield dimensions | 180 x 158 x 82mm / 7.1 x 6.2 x 3.2" (wxdxh) | | | | | |
| Housing | ABS plastic | | | | | |
| Pan size | 130mm Ø / 5.1" Ø | | | | | |
| Overall dimensions (wxdxh) | 195x240x70 mm / 7.7x9.4x2.8" | | | | | |
| Net weight | 1.2kg/2.6lb | | | | | |
| Other features | Low battery, stable and zero indicators | | | | | |



Optional Accessories

- In-Use Wet Cover



Adam Equipment have offices in the UK, USA and South Africa

www.adamequipment.com