
| REV. | CNN | CNN DESCRIPTION | Date | Check in | 01 - | 13/04/2010 | Shaun Barron | 01 - | - | 89/03/2013 | Shaun Barron |

Dimensions



Description

A cable socket in which the brass body is completely insulated from accidental touch. The attractive slimline styling is dark grey in colour, and will allow cables to be mounted either from the end or at right angles.

End mounting is via a removable end plug in the cap with grub screw fixing, whilst right angled mounting allows up to three cables to be soldered in by removing the long tab. A single cable is secured using the grub screw.

The end cap clips securely in place and is available in red or black for polarity indication. The socket will mate with any 4mm plug.

PART No' 595-0100 BLACK 595-0500 RED FEATURES MATERIAL

HOUSING:
CAPS:
BODY:
GRUB SCREW:

ABS , DARK GREY
ABS RED OR BLACK
BRASS (GOLD PLATED)
BRASS (GOLD PLATED)

CURRENT RATING: 10 Amps

CONTACT RES: 0.30 milli-ohms TEMPERARURE: -10°C TO + 80°C

FLAMMABILITY: UL94 V-0

CONNECTOR Tel No. +44(0)1724 273200 Website www.dem-uk.com DEBURR AND BREAK | DRAWN BY UNLESS OTHERWISE SPECIFIED: FINISH SEE NOTE THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DIMENSIONS ARE IN MILLIMETRES SHARP EDGES APPROVED BY LINE SOCKET ALPHA 3 MANUFACTURING. **Alpha** ROXBURGH R LINEAR TOLERANCE: ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION O HIRD ANGLE PROJECTION SHEET 1 OF 1 NO DECIMAL PLACES ±0.5mm IF IN DOUBT ASK ALPHA 3 MANUFACTURING IS PROHIBITED. DRAWING NO 1 DECIMAL PLACE ±0.25mm 01 DO NOT SCALE DRAWING SCALE 1:2 DEM Manufacturing Deltron Emcon House 2 DECIMAL PLACES ±0.125mm 595-Series Harareaves Way, Sawcliffe Ind. Park **DELTRON** Enclosures MATERIAL SEE NOTE ANGULAR TOLERANCE: +1° A4 Release