


ROHS-COMPLIANT

LTR	REV.	DESCRIPTION	DATE
△	B	ECR # 090616-7 ADD BAR CODE NO.	06/16/09'


USB 3.0 A/M 9PIN
INS:BLUE(PT 300C)

3000±30


USB 3.0 A/M 9PIN
INS:BLUE(PT 300C)



P1



TUSB-0189



P2

TUSB-0189

PIN OUT

P1			P2
1	RED		1 VCC
2	WHITE		2 -DATA
3	GREEN		3 +DATA
4	BLACK		4 GND_PWRrt
5	BLUE		8 SDP1-
6	YELLOW		9 SDP1+
7	D.W		7 SDP1_Drain
8	PURPLE		SDP2_Drain
9	ORANGE		5 SDP2-
	B.D		6 SDP2+
SHELL			SHELL

NOTE:

1.CABLE: UL-2725 [#28(7/0.127 T.C)×1P INS:Foam-PE+D.W(7/0.127 T.C)+AL/MY +Hot-melt-Mylar]×2C+#28(7/0.127 T.C)×1P INS:Polyolefin + #28(7/0.127 T.C)×2C INS:Polyolefin + AL/MY + B.D(85%) PVC JACKET; OD:5.2±0.15mm COLOR:BLACK(NK-K01) REV 3.0.

2.CONNECTOR:

P1 & P2: USB 3.0 A/M 9PIN CONTACT:30u",SHELL:NI-PLATED.

3.HOOD:MOLDED TYPE,PVC 45P, COLOR:BLACK(NK-K01).

4.ELECTRICAL TEST:

(1)100% OPEN SHORT & MIS WIRE TEST.

(2)CONTACT RESISTANCE 3 ohm Max .

(3)INSULATION RESISTANCE 10M ohm Min .

(4)HI-POT DC300V

5.PACKING: EACH PC / POLYBAG + BIG HEADER CARD + BAR CODE LABEL.

50 PCS / CARTON

△ 6.BAR CODE NO.: 7611990186389.

Tolerance	Inch	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

Rotronic co., LTD.

Title
USB 3.0 A/M - A/M CABLE

Customer P/N: 11.02.8971

Draw
FANNIE 06/16/09'

Chek

App'd Customer : T-RAG

Engr

Scale NONE Units M/M Third Angle Projection

Dwg No. 170-3590 REV:B Sheet.1/1