



## JB22 Jumper Bars

### Terminal Blocks Accessories

#### Features and Benefits

Screw jumper bars

#### Main Technical Data

	IEC	cULus - CSA	Ex e
Rated current	192 A	175 A	
Rated voltage	Standard use 1000 V	600 V	630 V
Alternated poles			Not authorized
Impulse withstand voltage	8000 V		
Protection	IP	NEMA	

Material Specifications	Insulating material	Brass
	Flammability	
	NF F 16 101	
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C
	Storage	-55 +110 °C
	Installing	-67 +230 F

#### Mounting Instructions

Screw

Tool		Allen Key Ø 4 mm Ø 0.157 in
Torque		2 Nm ± 0.4 17.7 lb.in ± 3.54

#### Ordering Details

##### JB22 Jumper Bars

Description		Type	Order Code	Pack <sup>(ing)</sup> pieces	Weight g (1 pce)
22 mm 0.866 in spacing	2 poles	JB22-2	1SNK 922 302 R0000	5	27.00
	3 poles	JB22-3	1SNK 922 303 R0000	5	43.30
	5 poles	JB22-5	1SNK 922 305 R0000	5	76.10
	10 poles	JB22-10	1SNK 922 310 R0000	5	157.40

#### JB22 Mounting Instructions



- With flat pliers, cut out the partitions on the terminal block insulating body. Be careful to not cut out the jumped terminal blocks at both ends of the assembly,
- Mount the jumper bar with the recommended tool and torque.