

SKINDICHT® Accessories metric

Sealing rings SKINDICHT® E-M, O-ring Perbunan® metric



SKINDICHT® E-M

Incised sealing rings can be individually adapted to various cable diameters by removing the appropriate sizes.



Technical Data

Material: CR

Standard colour: black

Temperature range: -20°C up to +80°C

Part number	Type / size M	Outer-Ø x borings mm	Thickness mm	PU pieces
SKINDICHT® E-M				
5210 0620	E-M 12	10,0 x 5	5,0	250
5210 0621	E-M 16	13,8 x 3/6/9	5,5	250
5210 0622	E-M 20	17,6 x 4/7/10/13	6,0	250
5210 0623	E-M 25	22,6 x 8,5/11,5/14,5/17,5	7,5	100
5210 0624	E-M 32	29,6 x 16/19/22/25	9,5	100
5210 0625	E-M 40	37,6 x 23/26/29/32	12,0	50
5210 0626	E-M 50	47,6 x 30/33/36/39	14,0	50
5210 0627	E-M 63	60,6 x 36/39/42/45	14,0	50

Perbunan® is a registered trademark of BAYER AG.

SKINDICHT® O-ring Perbunan metric

Perbunan O-rings provide safe sealing against oil, dust and water on the metric fastening thread of the connector to the housing.

For an optimum sealing of the converter SKINDICHT® ZSE-M12/16/20 x 1,5 we recommend the O-rings with thickness 1,5 mm.



Technical Data

Material: NBR, halogen-free ozone/ UV-resistant

Standard colour: black

Temperature range: -30°C up to +100°C

Part number	Type	Inner-Ø mm	Thickness mm	PU pieces
SKINDICHT® O-ring Perbunan®				
5310 2001	O M 12 x 1,5	9	1,5	100
5310 2011	O M 16 x 1,5	13	1,5	100
5310 2021	O M 20 x 1,5	17	1,5	100
5310 2000	O M 12 x 2,0	9	2,0	100
5310 2010	O M 16 x 2,0	13	2,0	100
5310 2020	O M 20 x 2,0	17	2,0	100
5310 2030	O M 25 x 2,0	22	2,0	100
5310 2040	O M 32 x 2,0	28	2,0	50
5310 2050	O M 40 x 2,0	36	2,0	50
5310 2060	O M 50 x 2,0	46	2,0	25
5310 2070	O M 63 x 2,0	57	2,0	25

Perbunan® is a registered trademark of BAYER AG.