




PG5 Component Plugs

Terminal Blocks Accessories



Features and Benefits

- Component holder compatible with 5.2 mm *0.205 in* spacing SNK feed-through terminal blocks,
- Fit components 16 x 16 x 8.5 mm *0.630 x 0.630 x 0.335 in* (not supplied with plug) such as resistors, diodes, varistors,
- Direct plug-in into the terminal blocks jumper channels,
- Maximum dissipated power: 2 W.

Main Technical Data

	IEC	cULus - CSA	Ex e
Rated current			
Rated voltage	Standard use 250 V		
Impulse withstand voltage	4000 V		
Protection	IP 20	NEMA 1	

Mounting Instructions

Plug In

Tool	
Torque	

Material Specifications

Insulating material	Polyamide		
Flammability	V0		
NF F 16 101	I2F2		
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F
	Storage	-55 +110 °C	-67 +230 F
	Installing	-5 +40 °C	-23 +104 F

Ordering Details

PG5 Component Plugs

Description	Type	Order Code	Pack ^(ng) pieces	Weight g (1 pce)
Components insertion between 2 blocks	Dark Grey	PG5-R2	1SNK 900 403 R0000	20 8.01

PG5 Accessories

Description	Type	Order Code	Pack ^(ng) pieces	Weight g (1 pce)
1 Blank card	White <input type="checkbox"/>	MC512	1SNK 140 000 R0000	22 0.06
Universal wire markers holder	Grey <input type="checkbox"/>	UMH	1SNK 900 611 R0000	10 0.20
Self adhesive strip	White <input type="checkbox"/>	SAT5	1SNK 900 614 R0000	5 6.00

PG5 Mounting Instructions



- Open the PG5-R2 with a flat screwdriver Dia. 3.5 mm *0.138 in*,
- Use a soldering iron to fix your component,
- Close the PG5-R2.