


Open Grommets



Specifications:

Maximum constant working temperature : 70°C.
 Minimum constant temperature : -35°C.
 Black PVC normal shore hardness : 43°C to 55°C.



Dimensions : Millimetres

Specification Table

Description	A	B	C	D	E	Part Number	
Grommet, 8mm, PK100	4.8	1.6	3.2	6.4	8.0	PV2 GROMMET PK 100	
Grommet, 9.5mm, PK100	6.4	1.2	4.8	6.0	9.5	PV710 GROMMET PK 100	
Grommet, 9.5mm, PK100		4.0	6.4	7.1		PV5 GROMMET PK 100	
Grommet, 9.5mm, PK100			4.8			6.4	PV6 GROMMET PK 100
Grommet, 11.1mm, PK100	8.0	1.6	4.8	6.4	11.1	PV24 GROMMET PK 100	
Grommet, 12.7mm, PK100	9.5			5.6	12.7	PV35 GROMMET PK 100	
Grommet, 12.7mm, PK100			6.4	4.8	14.3	PV36A GROMMET PK 100	
Grommet, 14.3mm, PK100				6.4		PV36 GROMMET PK 100	
Grommet, 13.5mm, PK100	10.3		7.5	6.4	13.5	PV45 GROMMET PK 100	
Grommet, 14.3mm, PK100			8.0		4.8	14.3	PV37A GROMMET PK 100
Grommet, 15.9mm, PK100	11.1		7.2	6.4	15.9	PV44 GROMMET PK 100	
Grommet, 15.9mm, PK100			8.0	4.8	14.3	PV50A GROMMET PK 100	
Grommet, 14.3mm, PK100	11.9		6.4	8.0	15.9	PV231 GROMMET PK 100	
Grommet, 15.9mm, PK100			9.5	6.8	17.5	PV233 GROMMET PK 100	
Grommet, 17.5mm, PK100		6.3		15.9	PV53 GROMMET PK 100		
Grommet, 15.9mm, PK100	12.7	11.1	6.4	19.0	19.0	PV64 GROMMET PK 100	
Grommet, 19mm, PK100	14.3				12.7	25.4	PV73A GROMMET PK 100
Grommet, 25.4mm Outside Diameter					15.9	23.8	PV73M GROMMET PK 100
Grommet, 23.8mm, PK100	20.0	19.0	7.5	30.0	30.0	PV93 GROMMET PK 100	
Grommet, 30mm Outside Diameter	25.4						

Dimensions : Millimetres

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-Power is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

