



Without locking ring.

With standard locking ring.

PANEL MOUNTING

SOLDER LUG

SPECIFICATIONS
ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10m Ω max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000M Ω min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30 ° C to 85 ° C.

MATERIALS
CASE: Dially phthalate (DAP) (UL94V-0).
ACTUATOR: Brass, chrome plated.
BUSHING: Brass, nickel plated.
HOUSING: Stainless Steel.
TERMINAL/CONTACT: Silver or gold plated.

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

SWITCH FUNCTION

Model No.	POS.1	POS.2	POS.3
	1MS2 Term. Comm.	ON	NONE
SCHEMATIC	2 Comm. 3 1 0	OPEN	2-1 1 0 2 Comm. 3 1

符號	原尺寸	修改後尺寸	變更日期
1 (A)			
2 (B)			
3 (C)			
4 (D)			
5 (E)			

SCALE (比例) : 3 : 2

TOLERANCE (公差) :
 0.00 mm ± 0.25mm
 0.0 mm ± 0.40mm
 ANGULAR : ± 2.54 mm
 FILE NAME : 1MSP0293

TITLE 圖名	Miniature Toggle Switches			SIZE 圖紙	A4
DWG NO. 圖號	1MS2T1B1M1QE			UNIT 單位	inch
REV. 版本	A	DATA 日期	SEP - 30 - 2002	SHEET 張數	1 of 1
CHECKED BY 審核	JACK			DRAWN BY 製圖	BLUE

德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.