





# PA108

**Tab-to-Tab  
Terminal Block (12 poles)**



## TECHNICAL DATA

	IEC Standards	American Standards
<b>Versions</b>	12 poles	
<b>Ratings</b>	450V - 15A (with 2.5 sqmm wire)	300V - 15A
<b>Wire Size</b>	According to the crimping 6.3 mm female tab insert, up to 2.5 sqmm	22 ÷ 12 AWG female tab insert
<b>Working Temperature</b>	- 5 ÷ 125°C (short time 155°C)	23 ÷ 221°F
<b>Plastic Material</b>	Polyamide PA6.6 natural colour, UL94 V2, GWT 960°C	
<b>Metal Parts</b>	6.3 x 0.8 tab insert made in zinc plated steel	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	E76048 vol. 1 sec. 10	300V - 15A - 105°C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	22 ÷ 12 AWG - 600V - 15A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING				
Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 108	300212	250	30x20x40	10.5

DIMENSIONAL  
DRAWING

