



PART NO.

## PSG01566

REVISIONS								
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	17/4/08	Suresh	17/4/08	G. C	01/5/08





## **Specifications:**

Maxmim rating : 100V ac 1A or 12V dc 2A.

Minimum insulation resistance : 50M ohm at 250V dc.

Dielectric strength : 250V ac/1 minute.

Maximum contact resistance : 30M ohm.

Maximum insertion force : 4.5kg.

Withdrawal force : 0.9kg to 3kg.

Materials:

Housing : Fibre + nylon.

Metal shell : Brass/nickel plated.

Contacts : Phosphor bronze, silver plated.

Dimensions: Millimetres

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was ware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from the regilgence. SPC pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2008.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Veena	17/04/08
CHECKED BY:	DATE:
Suresh	17/04/08
APPROVED BY:	DATE:
G.Cook	01/05/08

	DRAWING TITLE:							
	Chassis Plug - Mini DIN 4 P							
	SIZE	DWG NO.		l -	TRONIC FII	LE		REV
_	A 1280718_DWG			Α				
	SCALE: NTS		U.O.M.: mm		SHEET:	1	OF	2



PART NO.

PSG01566

REVISIONS								
ECN #	ECN # REV DESCRIPTION		DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	17/4/08	Suresh	17/4/08	G. C	01/5/08

## **Part Number Table**

Description	Part Number
Plug, Mini DIN, Chassis, 4P	PSG01566

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from lengligence or where the Group was aware of the possibility of such loss or damage arising is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-SIGNAL is the registered trademark of the Group. ® Premier Farnell ple 2008.

TOLERANCES:

UNLESS OTHERWISE
SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

DRAWN BY:	DATE:
Veena	17/04/08
CHECKED BY:	DATE:
Suresh	17/04/08
APPROVED BY:	DATE:
G.Cook	01/05/08

	DRAWI	NG TITLE:							
	Chassis Plug - Mini DIN 4 P								
	SIZE <b>A</b>	SIZE DWG NO.			ELECTRONIC FILE 1280718_DWG				
SCALE: NTS		E: NTS	U.O.M.: mm		SHEET:	2	OF	2	