



**ACCESSORIES HOUSING ENTRY/EXIT TUBES**

**TYPICAL APPLICATIONS**

**Housing entry/exit tubes for cables, with strain-relief ties**

- Control box wiring
- Automotive industry
- Machine construction

- Material: Neoprene
- Temperature range: -30°C to +90°C
- Flame-retardant, conforms to UL 514
- Includes cable tie for strong, secure and watertight strain-relief
- Highly elastic material allows passing of single wires
- Resistant to chemicals
- Weatherproof
- Simple and fast installation
- 5 sizes for cable diameters from 4 to 32 mm.

TECHNICAL INFORMATION												
PROD. REF.	PACKAGE QUANTITY	HEIGHT A	DIMENSIONS [mm]			FOR CABLE Ø FROM ... TO	FOR HOLE Ø [mm]	FOR WALL THICKNESS UP TO	MATERIAL	TIE TYPE	WEIGHT 100 PIECES	
			WIDTH B	D	E							
7401	10	18	23.5	13.0	5.0	4.0 – 09.0	16	2.2	Neoprene	TY 24 MX	420 g	
7402	10	18	27.5	13.0	5.0	7.0 – 12.0	20	2.2	Neoprene	TY 25 MX	690 g	
7403	10	22	37.5	17.0	5.0	12.0 – 18.0	25	2.2	Neoprene	TY 25 MX	1100 g	
7404	5	22	44.5	17.0	5.0	18.0 – 25.0	32	2.2	Neoprene	TY 25 MX	1500 g	
7405	5	24	51.0	18.0	6.0	25.0 – 32.0	38	2.2	Neoprene	TY 25 MX	1950 g	