



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS



DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
2063	A	RELEASED	JN	08/04/09	JWM	08/06/09	JWM	08/06/09





Dimension

Pad Layout



SPECIFICATION

1. Terminal pad Material: Pure Tin
2. Soldering characteristic: Meets EIA specs. RS 186-9E, ANSI/J-std-002 Category 3
3. Operating Current: 100mA~2.0A
4. Maximum Voltage: 6V~60V
5. Temperature Range: -40°C to 85°C



Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (T _{smax} to T _p)	3 C/second max.
Preheat :	
Temperature Min (T _{smin})	150 °C
Temperature Max (T _{smax})	200 °C
Time (t _{smin} to t _{smax})	60-180 seconds
Time maintained above:	
Temperature(TL)	217 °C
Time (tL)	60-150 seconds
Peak/Classification Temperature(Tp) :	260 C
Time within 5°C of actual Peak :	
Temperature (tp)	20-40 seconds
Ramp-Down Rate :	6 °C /second max.
Time 25°C to Peak Temperature :	8 minutes max.

Solder reflow


*Due to "Lead Free" nature, Temperature and Dwelling time for the soldering zone is higher than those for Regular. This may cause damage to other components.

1. Recommended max past thickness > 0.25mm.
2. Devices can be cleaned using standard methods and aqueous solvent.
3. Rework use standard industry practices.
4. Storage Environment : < 30°C / 60%RH

Caution:

1. If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.
2. Devices are not designed to be wave soldered to the bottom side of the board.

Reflow Profile



Mfg. P/N	A		B		C		D	Hold Current	Trip Current	Rated Voltage	Maximum Current	Typical Power	Max Time-to-Trip		Resistance Tolerance		Thermal Derating Curve Option	Time-to-Trip Curve Option
	Min	Max	Min	Max	Min	Max	Min	Ih, A	It, A	VMAX Vdc	IMAX A	Pd, W	A	Time	RMIN ohms	RIMAX ohms		
MC33187	4.37	4.73	3.07	3.41	0.6	0.9	0.3	0.14	0.3	60	10	0.8	8	0.008	1.2	6.5	Option B	Option B
MC33188	4.37	4.73	3.07	3.41	0.6	0.9	0.3	0.2	0.4	30	10	0.8	8	0.02	0.8	5	Option B	Option C
MC33190	4.37	4.73	3.07	3.41	0.35	0.65	0.3	0.5	1	16	40	0.8	8	0.15	0.15	1	Option B	Option E
MC33193	4.37	4.73	3.07	3.41	0.35	0.65	0.3	0.75	1.5	16	40	0.8	8	0.2	0.11	0.45	Option A	Option F
MC33196	4.37	4.73	3.07	3.41	0.25	0.55	0.3	1.1	2.2	8	100	0.8	8	0.3	0.04	0.21	Option A	Option G

DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jason Nash	08/06/09
CHECKED BY:	DATE:
JWM	08/06/09
APPROVED BY:	DATE:
JWM	08/06/09

DRAWING TITLE:			
Surface Mountable PTC Resettable Fuse			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	Ta-1192	Ta-1192.dwg	A
SCALE:	U.O.M.:	SHEET:	
NTS	INCHES [mm]	1 OF 1	