

1 2 3 4 5 6 7

A

B

C

D

E

PAP

0.33MAX
0.00MIN

6.10 +0.07
-0.06
3.25 ±0.10

DETAIL A

9.65 ±0.10

11.68 ±0.10

0.10

2.7 ±0.1

7.24 ±0.20

13.51 ±0.10

22.50 ±0.10

21.50 ±0.10

1.02 ±0.05

0.51 ±0.05

8.40 ±0.10

1.24MIN

0.56 ±0.05

1.02 ±0.03

1.02 ±0.02

DETAIL A

TUK Ltd
Unit 4, W.S.B.C. Riverside Rd
London SW17 0BA
Tel: 020 8946 6688
www.tuk.co.uk

SPECIFICATIONS:

- MATERIAL
HOUSING: POLYCARBONATE (PC),
CONTACT: PHOSPHOR BRONZE
FINE GOLD PLATED OVER NICKEL.
- MECHANICAL
CABLE TO PLUG TENSILE STRENGTH:
2010s MINIMUM.
DURABILITY: 200 MATING CYCLES MIN.

□ ELECTRICAL

- UL APPLICATIONS: 250 VOLTS AC
MAX. AT 2 AMPS,
DIELECTRIC WITHSTANDING VOLTAGE:
500 VOLTS AC,
INSULATION RESISTANCE: 500 MEGOHMS,
TERMINATION RESISTANCE: 35 MILLIOHMS
MAX. AFTER ENVIRONMENTAL TESTING.

CUSTOMER: TUK

APPD.	FILE	PG88X000BX00.DWG
CHKD.	DWG NO.	PG88X000BX00
DR.	TITLE	8P8C ?? "BN"?



A2	修改線孔尺寸(1.07改為1.02MM).			
A1	修改尺寸			
REV.	DESCRIPTION	ENG.	APPROVAL	

SCALE	/	SIZE
UNIT	MM	REV.

1 2 3 4 5 6 7