



| PIN OUT | |
|----------|----------|
| (HDD15M) | (HDD15M) |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 10 | 10 |
| 11 | 11 |
| 12 | 12 |
| 13 | 13 |
| 14 | 14 |
| 15 | 15 |
| SHELL | SHELL |

SPECIFICATION:

1. SHELL: STEEL, ZINC PLATED OR TIN PLATED
2. PIN CONTACT: GOLD PLATED OVER NICKEL
3. INSULATOR: PBT GLASS FIBRE REINFORCED
UL 94 V0
4. CURRENT RATING: 5 AMP
5. DIELECTRIC STRENGTH: 1000V FOR ONE MINUTE
6. INSULATOR RESISTANCE: 1000M MIN AT 500V DC
7. TEMPERATURE: -55°C - +105°C
8. PACKAGE: W/CLEAR POLYBAG

| 1-1 | REVISE CONNECTER | | |
|--------------------------|------------------|------------|-----------|
| 1-0 | | | |
| REV | DESCRIPTION | DATE | ECN NO |
| | | | |
| DWG NAME: SUPER THIN G.C | | | |
| G. W. NO | | CUS. ID: | |
| CUS. NO | | DWG. NO: | |
| SHEET: | 1/1 | TOLERANCE: | UNIT: mm |
| | | .X | |
| | | .XX ±0.40 | DRAW. BY: |
| | | SCALE: 1:1 | CHECKED |

400 9769