



• Designed to attach coax or telephone cable to the support strand 1/4" (6.4mm) or 5/16" (7.9mm) to form the expansion loop and keep equipment and cables clear of pole hardware

• One-piece construction with integral 1/2" (12.7mm) spacer reduces inventory costs of separate spacer and bands, and installs faster to lower the installed cost

• Releasable and reusable

| Part Number:<br>Product Family:<br>Product Line: | AST10-5-C100<br>Aerial Support Tie – Weather Resistant Polypropylene<br>Outside Plant |
|--|---|
| Product Line:                                    | POLYPROPYLENE Cable Ties  |
| RoHS Compliancy Status:                          | Compliant   |
| Part Description:                                | Aerial Support Tie, 5.6", Integral 1/2" spacer for support strand applications        |
| Product Type:                                    | Cable Ties  |
| Material:  | Weather Resistant Polypropylene   |
| Color:   | Black   |
| CSA Certified:                                   | No  |
| UL Listed (File #E56854):                        | No  |

| UL Recognized (File #E56854):      | No                  |
|------------------------------------|---------------------|
| Length (In.):                      | 5.6                 |
| Length (mm):                       | 142                 |
| Width (In.):                       | .448                |
| Width (mm):                        | 11.4                |
| CE Compliant:                      | Yes                 |
| Head Width (In.):                  | 1.16                |
| Head Width (mm):                   | 29.5                |
| Locking Style:                     | Releasable          |
| Material Flammability Rating:      | UL94 HB             |
| Max. Bundle Diameter (In.):        | 1.00                |
| Max. Bundle Diameter (mm):         | 25                  |
| Max. Continuous Use Temperature:   | 239°F (115°C)       |
| Min. Loop Tensile Strength (Lbs.): | 75                  |
| Min. Loop Tensile Strength (N):    | 334                 |
| Std. Pkg. UOM:                     | РК                  |
| Thickness (In.):                   | .055                |
| Thickness (mm):                    | 1.4                 |
| Tool:                              | Hand Installed Only |

| UOM: | PC |
|------|----|
|------|----|

Std. Pkg. Qty.: 100

Min. Order Qty.: 100