

Dimensions: Millimetres (Inches)

- L										
- 1	(the 'Group') of are incensed to it. No incence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:					
		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Veena	06/05/10	BNC Right Angle PCB Mount Jack Receptacle					
			CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE 1712355 DWG		REV	
			Jagan	06/05/10	Δ	M10002425			A	
			APPROVED BY:	DATE:		U.O.M.: mm (Inches)				
			Farnell	20/05/10	SCALE: NTS			SHEET: 1	OF 2	

	PART NO.		REVISIONS								
🔊 multicomp	13-60-6 DGZ	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
		-	А	RELEASED	Veena	06/05/10	Jagan	20/05/10	Farnell	20/05/10	

## Specifications:

Mechanical Characteristics:	
Mating/unmating	: 500 Cycles.
Electrical Characteristics:	
Normal impedance	: 50Ω.
Frequency range	: 0-1GHz.
Testing voltage	: 500 Volts RMS.
Dielectric withstanding voltage	: 1500 Volts RMS.
Minimum insulation resistance	: 5000MΩ.
Environmental Characteristics:	
Temperature range	: -40°C to +60°C.
Thermal shock	: MIL-STD-202, Method 107, Cond. B.
Physical shock	: MIL-STD-202, Method 204, Cond. B.

## Specification Table

Item	Description	Material	Part Number			
1	Mounting Post	Brass				
2	Body	Zinc Alloy				
3	Nut Brass					
4	Washer	S50C	13-60-6 DGZ			
5	Insulation	Polypropylene UL 94HB				
6	Centre Contact	Phosphorous Bronze with Gold Plating at Contact Area Tin Plating at Tail				
7	Solder Pin	Copper Wire				

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

(the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:						
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with-	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Veena	06/05/10	BNC Rigi	BNC Right Angle PCB Mount Jack Receptacle					
believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this		CHECKED BY:	DATE:	SIZE DWG NO.	E		LECTRONIC FILE		REV	
data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or		Jagan	06/05/10	Δ	M10002425	1712355 DWG			A	
childed. Elability for loco of damage robatility for any for allo internation of		APPROVED BY:	DATE:		U.O.M.: mm (Inches)				4	
or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Farnell plc 2010.		Farnell	20/05/10	SCALE: NTS			SHEET:	2 OF	F 2	