

Sta-Kon® Terminals



These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wire's flex point. Brazed seam barrel is serrated for high pull-out value. Terminal is high conductivity electrolytic copper, electro-tin plated. Insulation is color-coded.


Stock thickness same as ring terminal of same size.

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages K61- K62. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Vinyl Insulated Fork – Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
						A	B	C	M
18RA-6F	100	22-16	.150	#6	5	.94	.25	.27	.81
RA1167	1000	22-16	.150	#6	5	.94	.25	.27	.81
18RA-8F	100	22-16	.150	#8	5	.97	.31	.27	.81
RA1147	1000	22-16	.150	#8	5	.97	.31	.27	.81
18RA-10F	100	22-16	.150	#10	5	.97	.31	.27	.81
RA1157	1000	22-16	.150	#10	5	.97	.31	.27	.81
14RB-6F	100	18-14	.170	#6	6	.97	.31	.27	.81
RB647	1000	18-14	.170	#6	6	.97	.31	.27	.81
14RB-6FS	100	18-14	.170	#6	6	.89	.30	.25	.75
14RB-8F	100	18-14	.170	#8	6	.97	.31	.27	.81
RB657	1000	18-14	.170	#8	6	.97	.31	.27	.81
14RB-10F	100	18-14	.170	#10	6	.97	.31	.27	.81
RB1157	1000	18-14	.170	#10	6	.97	.31	.27	.81
14RB-14F	100	18-14	.170	1/4"	6	1.11	.44	.38	.89
RB1717	1000	18-14	.170	1/4"	6	1.11	.44	.38	.89
10RC-6F	50	12-10	.210	#6	7	1.09	.38	.27	.90
RC1337	500	12-10	.210	#6	7	1.09	.38	.27	.90
10RC-8F	50	12-10	.210	#8	7	1.09	.38	.27	.90
RC1147	500	12-10	.210	#8	7	1.09	.38	.27	.90
10RC-10F	50	12-10	.210	#10	7	1.09	.38	.27	.90
RC1157	500	12-10	.210	#10	7	1.09	.38	.27	.90
10RC-14F	50	12-10	.210	1/4"	7	1.15	.50	.37	.90
RC1167	500	12-10	.210	1/4"	7	1.15	.50	.37	.90

U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003



Fork terminals allow easy installation since the mounting screw does not have to be completely removed. Catalog numbers with the suffix X indicate an expanded insulation support. This means a wider wire entry to accommodate heavy wall insulation.


Stock thickness same as ring terminal of same size.

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages K61- K62. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Vinyl Insulation Fork – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
						A	B	C	M
18RA-6FX	100	22-16	.170	#6	5	.94	.25	.27	.81
RA1167-170	1000	22-16	.170	#6	5	.94	.25	.27	.81
18RA-8FX	100	22-16	.170	#8	5	.97	.31	.27	.81
RA1147-170	1000	22-16	.170	#8	5	.97	.31	.27	.81
18RA-10FX	100	22-16	.170	#10	5	.97	.31	.27	.81
RA1157-170	1000	22-16	.170	#10	5	.97	.31	.27	.81
14RB-6FX	100	18-14	.200	#6	6	.97	.31	.27	.81
RB647-200	1000	18-14	.200	#6	6	.97	.31	.27	.81
14RB-8FX	100	18-14	.200	#8	6	.97	.31	.27	.81
RB657-200	1000	18-14	.200	#8	6	.97	.31	.27	.81
14RB-10FX	100	18-14	.200	#10	6	.97	.31	.27	.81
RB1157-200	1000	18-14	.200	#10	6	.97	.31	.27	.81
10RC-8FX	50	12-10	.250	#8	7	1.11	.38	.27	.90
RC1147-250	500	12-10	.250	#8	7	1.11	.38	.27	.90
10RC-10FX	50	12-10	.250	#10	7	1.11	.38	.27	.90
RC1157-250	500	12-10	.250	#10	7	1.11	.38	.27	.90
10RC-14FX	50	12-10	.250	1/4"	7	1.17	.50	.37	.90

U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG2001, ERG2003



K
Sta-Kon®

Thomas & Betts