



Miniblocks for EN 50045 (DIN 46277/2) rail

Screw clamp ~ DIN 2


DR 4/6.... - 4 mm² blocks - 6 mm .236" spacing




DR 4/6




DR 4/6.1



BADRL



FEDR61



SCDR61



BJM62

Characteristics

| | | IEC NFC DIN | UL | CSA |
|------------------------------------|-----------------------|-------------------|-----------|-----------|
| Wire size mm ² / AWG | Solid | 0.2 - 4 | 18-12 AWG | 18-12 AWG |
| | Stranded | 0.22 - 4 | | |
| Voltage | V | 500 Gr.C | 250 | 300/150 |
| Current | A | 30 | 20 | 10/25 |
| Rated wire size | mm ² / AWG | 4 mm ² | 12 AWG | 12 AWG |
| Wire stripping length | mm / inches | 9.5 mm / .37" | | |
| Recommended screwdriver | Nm / lb.in | 4 mm / .16" | | |

Selection

| Description | Type | Order P/N | Packaging Weight kg |
|---------------------------------|-------------------------------------|--------------------|------------------------|
| DIN 2 standard block grey | <input type="checkbox"/> DR 4/6 | 1SNA 110 251 R0500 | 50 |
| DIN 2 standard block blue | <input type="checkbox"/> DR 4/6.N | 1SNA 120 251 R0700 | 50 |
| DIN 2 block with partition grey | <input type="checkbox"/> DR 4/6.1 | 1SNA 110 491 R1700 | 50 |
| DIN 2 block with partition blue | <input type="checkbox"/> DR 4/6.1.N | 1SNA 120 491 R1100 | 50 |

Accessories

| | | | | |
|---|--------------------------------|---------------|--------------------|----|
| End stop V0 | | BADRL 6.5 mm | 1SNA 199 420 R2100 | 50 |
| End section | grey <input type="checkbox"/> | FEDR61 1 mm | 1SNA 117 600 R0300 | 25 |
| | blue <input type="checkbox"/> | FEDR61 1 mm | 1SNA 127 600 R0500 | 10 |
| Circuit separator | white <input type="checkbox"/> | SCDR61 0.3 mm | 1SNA 173 016 R1000 | 25 |
| Assembled jumper bar (without IP20 protection) | 2 poles | BJM62 32 A | 1SNA 173 217 R2600 | 10 |
| | 3 poles | BJM62 32 A | 1SNA 173 218 R0700 | 10 |
| | 5 poles | BJM62 32 A | 1SNA 173 219 R0000 | 10 |
| | 10 poles | BJM62 32 A | 1SNA 173 221 R2200 | 10 |
| | | BJM62 32 A | 1SNA 173 226 R2700 | 10 |

DR 4/6.P - 4 mm² ground block - 6 mm .236" spacing

Characteristics


| | | IEC NFC DIN | UL | CSA |
|------------------------------------|-----------------------|--------------------------------|-------------|-------------|
| Wire size mm ² / AWG | Solid | 0.2 - 4 | 18 - 12 AWG | 18 - 12 AWG |
| | Stranded | 0.22 - 4 | | |
| Rated wire size | mm ² / AWG | 4 mm ² | 12 AWG | 12 AWG |
| Wire stripping length | mm / inches | 9.5 mm / .37" | | |
| Recommended screwdriver | Nm / lb.in | 4 mm / .16" | | |
| Recommended torque | Nm / lb.in | 0.5 - 0.8 Nm / 4.4 - 7.1 lb.in | | |

Selection

| Description | Type | Order P/N | Packaging Weight kg |
|---------------------------------|-----------------------------------|--------------------|------------------------|
| Ground DIN 2 block green/yellow | <input type="checkbox"/> DR 4/6.P | 1SNA 160 496 R2600 | 50 |

Accessories


| | | | | |
|-------------------|---------------------------------|---------------|--------------------|----|
| End stop V0 | | BADRL 6.5 mm | 1SNA 199 420 R2100 | 50 |
| End section | yellow <input type="checkbox"/> | FEDR63 1 mm | 1SNA 103 975 R2100 | 25 |
| Circuit separator | white <input type="checkbox"/> | SCDR61 0.3 mm | 1SNA 173 016 R1000 | 25 |




DR 4/6.P



BADRL



FEDR63



SCDR61