

SAFETY DATA SHEET

DEB CONTECT

Page 1 Issued: 24.08.04

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: DEB CONTECT

Use / description of product: Service Spray

Company name: DEB Ltd

108 Spencer Road

Belper Derbyshire DE56 1JX

Tel: 01773 596700 Fax: 01773 820482

2. COMPOSITION / INFORMATION ON INGREDIENTS

Contains: Aliphatic / Aromatic Hydrocarbon CAS No: 64742-47-8 EINECS No: 265-149-8 [Xn] [N]

R38, 65, 51/53

Nonylphenol polyglycol ether 1-7 EO CAS No: 9016-45-9 EINECS No: Polymer [Xi] R36/38

53

Iso Butanol CAS No: 78-83-1 EINECS No: 201-148-0 [Xi] R10 37/38 41 67

3. HAZARDS IDENTIFICATION

Main hazards: Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Unlikely to cause irritation on single contact. Prolonged or repeated contact may cause short

term irritation.

Eye contact: There may be irritation and redness.

Ingestion: Ingestion of large amounts may cause irritation with diarrhoea and vomiting. May cause lung

damage if swallowed.

Inhalation: Fumes or vapour may cause irritation, nausea or drowsiness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash contaminated skin immediately with soap and water. Remove contaminated clothing and

launder before re-use.

Eye contact: Wash immediately with clean water for at least 10 minutes. If any soreness or irritation persists

seek medical advice.

Ingestion: Rinse mouth and throat thoroughly. Give about 1/2 pint of liquid to drink. Obtain immediate

medical advice. DO NOT INDUCE VOMITING DUE TO THE DANGER OF ASPIRATION.

Inhalation: Remove to fresh air and seek medical advice if symptoms persist.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Issued: 24.08.04

SAFETY DATA SHEET

DEB CONTECT Page 2

Protection of fire-fighters: Protect containers from heat by cooling with water spray. Wear self-contained breathing

apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Treat

any spillage as a fire hazard. Spray, vapour or mist can be apotential fire or explosion hazard.

May cause damage to surfaces making them slippery.

Environmental precautions: Dispose of as special waste. Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand. Place in plastic barrels for disposal. Dispose of as special waste.

7. HANDLING AND STORAGE

Handling requirements: Wear suitable personal protective equipment, as detailed in section 8. Ensure there is sufficient

ventilation of the area. Do not handle in a confined space. If the product is to be used for an application other than that stated on the label, contact Technical Services Hotline (01773

880367) to check suitability.

Storage conditions: Protect from extremes of temperature.Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

TWA (8 hr exposure limit): 800mg/cubic metre (OES)

Engineering measures: Monitor exposure using suitable equipment such as Drager Air Pump. Ensure TWA is not

exceeded. Ensure any spills do not enter watercourses or drainage systems.

Respiratory protection: Unlikely to be required in normal use. Use in well ventilated area. It is suggested that exposure

is kept within the Occupational Exposure Limits for vapours established by the Reciprocal Calculation Procedure for mixed exposures to hydrocarbon solvents in HSE Guidance Note

EH40: (8 hour TWA reference period) - 800 mg/cubic metre.

Hand protection: Wear nitrile or plastic coated solvent resistant gloves. Take further advice from reputable glove

 $maufacturer \ / \ supplier \ regarding \ suitability \ / useful \ contact \ time \ of \ their \ recommended \ gloves.$

Eye protection: Wear suitable eye protection such as safety goggles or a face shield.

Skin protection: Not required under normal conditions or unless contact is prolonged.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Brown

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

Viscosity: Non-viscous

Flash point°C: 70

pH: Not Applicable

Issued: 24.08.04

SAFETY DATA SHEET

DEB CONTECT Page 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: At temperatures above the flash point, flammable vapours are produced.

Materials to avoid: Strong oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Inhalation - May cause irritation to eyes, nose and throat following exposue to mists, vapours

and fumes. Skin Contact- May cause irritation / dryness or defatting of the skin with prolonged

contact. Eye contact- Irritant and may cause inflammation. Ingestion - May cause

gastrointestinal inflammation. DO NOT INDUCE VOMITING DUE TO THE DANGER OF

ASPIRATION.

12. ECOLOGICAL INFORMATION

Mobility: Non-volatile. Insoluble in water. Floats on water.

Persistence and degradability: Aquatic Pollutant. Do not allow to enter water courses or sewers. Expected to biodegrade

slowly.

Bioaccumulative potential: Bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Unwanted material should be disposed of as hazardous waste by registered contractor.

Disposal of packaging: Drain well. Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

Shipping name: Not classified for transport

IMDG / IMO

EmS: - Marine pollutant:

IATA / ICAO

15. REGULATORY INFORMATION

Hazard symbols: Harmful.

Dangerous for the environment.





Risk phrases: R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

R65: Harmful: may cause lung damage if swallowed.

DEB CONTECT

Safety phrases: S2: Keep out of the reach of children.

S24/25: Avoid contact with skin and eyes.

S35: This material and its container must be disposed of in a safe way.

S37/39: Wear suitable gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Additional information: For additional information regarding Deb products please contact the Deb Technical Services

Department (01773 880367). In all cases of potential poisoning supportive therapy is of the utmost importance. If medical professionals require advice regarding first aid treatment all Deb products are registered at Guys Hospital, London. The above information complies with the 199/45/EC Directive and it's ammendments. Always ensure users are fully trained and read label before using product. Data Compiled using Raw Material Supplier Data and Lycos

Classification System. Reason for re-issue - update of transport information

Legal disclaimer: The purpose of the above information is to describe the products only in terms of health and

safety requirements. The information given should not, therefore, be construed as guaranteeing

specific properties or as specification. Customers should satisfy themselves as to the suitability

and completeness of such information for their own particular use.