

PART NO.


SACK2S

REVISIONS

ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	A	RELEASED	Naveen	18/09/09	Jagan	18/09/09	Farnell	02/10/09

Features:

- RJ45 complies with FCC part 68 standard.
- Jack insertion life >750 mating cycles.
- IDC insertion life >250 mating cycles.
- Operating temperature : -40°C to +60°C.



Dimensions : Millimetres

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2009.

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Naveen	18/09/09
CHECKED BY:	DATE:
Jagan	18/09/09
APPROVED BY:	DATE:
Farnell	02/10/09

DRAWING TITLE:			
RJ45 Coupler - CAT6, Shielded, Panel Mount			
SIZE	DWG NO.	ELECTRONIC FILE	REV
A		1761168-DWG	A
SCALE: NTS		U.O.M.: mm	SHEET: 1 OF 2



PART NO.

SACK2S

REVISIONS

ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	A	RELEASED	Naveen	18/09/09	Jagan	18/09/09	Farnell	02/10/09

Electrical:

Contact resistance : 20M ohms.
 DC current rating : 1.5A.
 Maximum DC resistance : 1.0 ohms.
 Insulation resistance : 500M ohms.
 Dielectric withstanding voltage : 100V.

Technical Data:

Category : CAT.6.
 Housing : ABS UL94V-0.
 Contact : 0.46mm diameter phosphor bronze gold plated over nickel.
 Gold plating : 1.27µm/50µ inch.
 Colour : Other.
 Type of product : Metalized shielded.

Part Number Table

Description	Part Number
Coupler, RJ45, CAT6, Shielded	SACK2S

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2009.

**TOLERANCES:
 UNLESS OTHERWISE SPECIFIED,
 DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.**

DRAWN BY:	DATE:
Naveen	18/09/09
CHECKED BY:	DATE:
Jagan	18/09/09
APPROVED BY:	DATE:
Farnell	02/10/09

DRAWING TITLE:			
RJ45 Coupler - CAT6, Shielded, Panel Mount			
SIZE	DWG NO.	ELECTRONIC FILE	REV
A		1761168-DWG	A
SCALE: NTS		U.O.M.: mm	SHEET: 2 OF 2