

V RANGE



FEATURES

- Wall or window mounting
- Single speed thermal overload protected motor
- Moulded in white and dove grey ABS plastic
- Integral electrical connector/isolator

TERMINOLOGY

A	Complete with time delay automatic shutters
R	Reversible motor (intake/extract)
I	Flush fitting/recessed. Wall mount only
M	Manual operation complete with pull cord operated shutters

MODELS

Type	Code	Farnell code	Specification
V15/6M	12780	7003456	Extract capacity 220 m ³ /hr (61.1 l/s). Watts 30. dBA @ 3m 43. 210mm high x 210mm wide x 93mm deep (when fitted)
V15/6A	12620	7003468	Extract capacity 220 m ³ /hr (61.1 l/s). Watts 34. dBA @ 3m 43. 210mm high x 210mm wide x 93mm deep (when fitted)
V23/9M	12790	7003470	Extract capacity 620 m ³ /hr (172.2 l/s). Watts 33. dBA @ 3m 43. 291mm high x 291mm wide x 128mm deep (when fitted)
V23/9AR	12760	7003481	Extract capacity 620 m ³ /hr (172.2 l/s). Watts 37. dBA @ 3m 46. 291mm high x 291mm wide x 128mm deep (when fitted)
V30/12AR	12770	7003493	Extract capacity 1125 m ³ /hr (312.5 l/s). Intake capacity 750 m ³ /hr (208.3 l/s). Watts 74. dBA @ 3m 56. 370mm high x 370mm wide x 142mm deep (when fitted)
V15/6AI	12730	7003055	Extract capacity 220 m ³ /hr (61.1 l/s). Watts 34. dBA @ 3m 43 306mm high x 290mm wide x 13.5mm deep (when fitted)