

**32412 Hook-up/Lead - UL AWM Style 3074**

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

**Description:**

The glass braid offers abrasion resistance, is treated to prevent fraying. The Silicone insulation strips easy and clean. Recommended for high-temperature applications in motors, lighting fixtures, clothes dryers, stoves, therapeutic and electronic devices

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Conductors	1
Total Number of Conductors	1
AWG	12
Stranding	19x24.5

**INSULATION:**

Insulation Material	Silicone with Lacquered Glass Braid Covering
Insulation Thickness	.030 in.

**OVERALL:**

Overall Nominal Diameter	.190 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Non-UL Temperature Rating	200°C
Recommended Maximum Baking Cycles	24 hours @ 410°F (210°C)
Bulk Cable Weight	25 lbs/1000 ft.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

UL AWM Style	3074
UL Rating	600 V, 200°C, VW-1
CSA Type	SEW-2
CSA Rating	600 V, 200°C
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**PUT-UPS AND COLORS:**

**32412 Hook-up/Lead - UL AWM Style 3074**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
32412 009500	#12 SIL GL BRD 200C 600V	500	17.5	WHITE	F
32412 010500	#12 SIL GL BRD 200C 600V	500	17.5	BLACK	F

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

Revision Number: 1      Revision Date: 04-29-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.