

PRODUCT INFORMATION

PART NUMBER:

7003743 (varies with colour and packing).

DESCRIPTION:

7-core Trailer Cable: 1 x 28/0.3mm + 6 x 14/0.3mm Plain Copper, PVC Insulated, PVC Sheathed, BS6862, Table E, Black.
Packing: 100m (Farnell) Drums.

CONDUCTORS:

Plain annealed copper bunch meeting the requirements of BS 6360 where applicable, and BS 6862.
6 cores, 1.0mm² (14/0.3mm).
1 core, 2.0mm² (28/0.3mm).

INSULATION:

Type T11 PVC compound meeting the requirements of BS 7655.
Minimum average radial thickness = 0.6mm.

LAY UP:

Centre, (28/0.3mm), White.
Outer, (14/0.3mm), Red, Green, Brown, Blue, Black, Yellow.

SCREEN:

Not Applicable.

SHEATH:

Type 6 PVC compound meeting the requirements of BS 7655.
Minimum average radial thickness = 0.8mm.
Minimum overall diameter = 9.7mm.
Maximum overall diameter = 10.2mm.

SERVICE DATA:

For use in road vehicles.

Maximum Rated Voltage: 100V.
Maximum conductor operating temperature: 70°C.
Approximate Mass/Unit Length: 183kg/km.