



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

| CHARACTERISTICS          |          |
|--------------------------|----------|
| OPERATING FORCE          | 7 LB MAX |
| RELEASE FORCE            | 2 LB MIN |
| DIFFERENTIAL TRAVEL      | .020 MAX |
| OVERTRAVEL               | .219 MIN |
| RELEASE TRAVEL           | .015 MIN |
| SWITCH-BASIC REPLACEMENT | 2 MNI    |

| ELECTRICAL DATA  |
|--|
| CONTACT ARRANGEMENT<br>(SEE CIRCUIT DIAGRAM)   |
| 10A-120, 240, OR 480 VAC; 1/3 HP - 120 VAC<br>3/4 HP - 240 VAC; 0.8A - 115 VDC; 0.4A - 230 VDC<br>.1A - 550 VDC<br>PILOT DUTY: 600 VAC MAX |

| SCALE  | 1/2 TO 1 |
|--|----------|
| DO NOT SCALE PRINT                                 |          |
| UNLESS OTHERWISE NOTED<br>DIMENSIONS ARE IN INCHES |          |
| TOLERANCES ARE:                                    |          |
| ONE PLACE (.0)                                     | ±.030    |
| TWO PLACE (.00)                                    | ±.015    |
| THREE PLACE (.000)                                 | ±.003    |
| ANGLES   | ±        |
| WEIGHT   |          |

NOTE -  
 ② SEAL TO BE FURNISHED BY USER  
 ③ - ROLLER ASSEMBLY MAY BE RE-ASSEMBLED 90° FROM POSITION SHOWN

DRAWING NUMBER: 5LS1  
 ISSUE: II  
 REVISIONS:  
 A CO15200 RE A JUN 65  
 CO23403 M B S SEP 68  
 CO24612 R E R OCT 68  
 CO25152 G C H APR 69  
 CO50352 K A G FEB 83  
 CO53005-D C J H AUG 84  
 CO65814-E G R T NOV 90  
 R E R 18 JUN 85  
 CHECKED: [initials]  
 DRAWN: [initials]