

9271 Twinax - Computer & Instrumentation Cable



Description:

124 Ohm twinaxial cable, 25AWG stranded (7x33) tinned copper, polyethylene insulation, Beldfoil® shield 100% coverage + 22 AWG stranded (7x30) stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	25
Stranding	7x33
Conductor Diameter	.021 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
Insulation Diameter	.083 in.

PAIR:

Pair Diameter	.170 in.
---------------	----------

Pair Color Code Chart :

Number	Color
1	Blue & Clear

OUTER SHIELD:

Outer Shield Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

9271 Twinax - Computer & Instrumentation Cable

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.240 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
Bulk Cable Weight	25 lbs/1000 ft.
Max. Recommended Pulling Tension	17 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	Style 2095

FLAME TEST:

UL Flame Test	1581 Vertical Tray
---------------	--------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	124 Ohms
Nom. Inductance	0.188 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	12.2 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	22.0 pF/ft
Nominal Velocity of Propagation	66 %
Nominal Delay	1.54 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	31.8 Ohms/1000 ft
Nominal Outer Shield DC Resistance	12 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
Nominal Attenuation	1			0.6
	10			1.7
	50			3.6
	100			5.0
	200			6.9
	400			9.6

Max. Operating Voltage - UL	300 V RMS
-----------------------------	-----------

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
------	-------------	--------------	--------------------	--------------	-------



9271 Twinax - Computer & Instrumentation Cable

9271 006100	TW PR FS PVC	100	3.2	BLUE, LIGHT	
9271 0061000	TW PR FS PVC	1000	28	BLUE, LIGHT	C
9271 006500	TW PR FS PVC	500	14	BLUE, LIGHT	
9271 006U1000	TW PR FS PVC	U1000	27	BLUE, LIGHT	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 12-06-2002

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.
All sales of Belden products are subject to Belden's standard terms and conditions of sale.