

## SOLDER DISPENSERS

146-706

Two grades of solder on a dispenser are offered by TBA. These are 60/40 (22 SWG) and Savbit (18 SWG).

The dispenser delivers the solder in a much more manageable quantity, thus making it easier to use.

The dispensers deliver the 60/40 and Savbit solders in 6m and 4m lengths respectively.

### DATA

<u>Solder Grade</u>	<u>Melting Temp.</u>		<u>Recommended Min. Junction Temp.</u> (°C)	<u>Electrical Conductivity</u> % IAC
	<u>Solidus</u> (°C)	<u>Liquidus</u> (°C)		
Savbit	183	215	275	10.9
60/40	183	188	248	11.5

### HANDLING AND USE PRECAUTIONS

Use these products in a well ventilated area. Fumes evolved during soldering should be extracted away from the operator.

Avoid inhaling fumes during soldering.

Wash hands thoroughly with soap and warm water after handling solder, particularly before eating and drinking or smoking.

Information in this publication and otherwise supplied to users is based upon our general experience and is given in good faith, but because of the particulars which are outside our knowledge and control and affect the use of the product, no warranty is given or is implied with respect to such information. Freedom from patent rights must not be assumed.

**TBA** Industrial Products Ltd.

P.O.Box 40 Rochdale Lancs  
OL12 7EQ Tel. (0706) 47422  
Telex 63174 Fax: (0706) 46170

**T&N**