


640 Signal Tower KombiSIGN 71

High protection rating IP 65
 Signal tower system 70 mm ø with
 modular construction
 Improved illumination
 Flexible combination of optical and audible elements



Order specification:

Permanent light element	12 - 240 V
red	641 100 00
green	641 200 00
yellow	641 300 00
clear	641 400 00
blue	641 500 00



Blinking light elementelement	24 V ==	115 V ==	230 V ==
red	642 100 75	642 100 77	642 100 78
green	642 200 75	642 200 77	642 200 78
yellow	642 300 75	642 300 77	642 300 78
clear	642 400 75	642 400 77	642 400 78
blue	642 500 75	642 500 77	642 500 78

Flashing light element	24 V =	115 V ~	230 V ~
red	643 100 55	643 100 67	643 100 68
green	643 200 55	643 200 67	643 200 68
yellow	643 300 55	643 300 67	643 300 68
clear	643 400 55	643 400 67	643 400 68
blue	643 500 55	643 500 67	643 500 68

LED-Permanent light element	24 V ==	115 V ~	230 V ~
red	644 100 75	644 100 67	644 100 68
green	644 200 75	644 200 67	644 200 68
yellow	644 300 75	644 300 67	644 300 68
clear	644 400 75	644 400 67	644 400 68
blue	644 500 75	644 500 67	644 500 68



LED-Blinking light element	24 V ≈	115 V ~	230 V ~
red	644 110 75	644 110 67	644 110 68
green	644 210 75	644 210 67	644 210 68
yellow	644 310 75	644 310 67	644 310 68
clear	644 410 75	644 410 67	644 410 68
blue	644 510 75	644 510 67	644 510 68
LED-redating light element	24 V ≈		
red	644 130 75		
green	644 230 75		
yellow	644 330 75		
clear	644 430 75		
blue	644 530 75		



Order specifications: Adapter

	CAGE CLAMP	Screw connection
Terminal element for tube mounting, including cap	640 810 00	640 830 00
Terminal element for bracket or base mounting, including cap and seal	640 800 00	640 820 00

Terms and Conditions - Imprint

Werma Signaltechnik GmbH + Co.KG · Dürbheimer Straße 15 · D-78604 Rietheim-Weilheim
 Tel. ++49 (0) 74 24 / 95 57-0 · Fax. ++49 (0) 74 24 / 95 57-44 · eMail: info@werma.de