


## Features

- .250" (6.35mm) Quick Connect Terminals
- Industry Standard Pinout
- SPST & SPDT Versions
- Flange Mount – "F" Suffix
- PC Board Mount – "P" Suffix



SPST-NO, 1 Form "A" SPDT, 1 Form "C"



### Contact Rating @ 14VDC

Maximum Load Current	50 Amp Rated		70 Amp Rated
	SPST-NO	SPDT	SPST-NO
Resistive Load	50A	50A (NO); 30A (NC)	70A

### DC OPERATED

NTE Type No.	Nom. Volt.	Contact Arr.	Coil Res. Ohms (Typ)	Nom. Power	Max. Contact Cur. @ 14VDC	Diag No.
R51-1D40-12	12VDC	SPST-NO	90	1.6W	50A	D38
R51-1D40-12F	12VDC	SPST-NO	90	1.6W	50A	D38
<b>NEW</b> R51-1D40-24	24VDC	SPST-NO	360	1.6W	50A	D38
<b>NEW</b> R51-1D40-24F	24VDC	SPST-NO	360	1.6W	50A	D38
R51-5D40-12	12VDC	SPDT	90	1.6W	50A	D38
R51-5D40-12F	12VDC	SPDT	90	1.6W	50A	D38
<b>NEW</b> R51-5D40-24	24VDC	SPDT	360	1.6W	50A	D38
<b>NEW</b> R51-5D40-24F	24VDC	SPDT	360	1.6W	50A	D38
R51-1D70-12	12VDC	SPST-NO	90	1.6W	70A	D38a
R51-1D70-12F	12VDC	SPST-NO	90	1.6W	70A	D38a
R51-1D70-12P	12VDC	SPST-NO	90	1.6W	70A	D38b
<b>NEW</b> R51-1D70-24	24VDC	SPST-NO	360	1.6W	70A	D38a
<b>NEW</b> R51-1D70-24F	24VDC	SPST-NO	360	1.6W	70A	D38a


### ACCESSORIES

MOUNTING STYLES	DESCRIPTION	NTE TYPE NO.
PC MOUNT	5-PIN	R95-160 (50 Amp ONLY)
WIRE LEADS	5-PIN	R95-188 (50 Amp ONLY)
WIRE HARNESSING	4-PIN	R95-160A (70 Amp ONLY)


# R51 Series

50 Amp and 70 Amp, SPST and SPDT Relays for use in Automotive/Marine/Tractor/Lawn Mower/Rec. Vehicles/Golf Cart Applications.


## D38



## D38a



## D38b



## Electrical Specifications

### Contact

Contact Material: AgSnO alloy

Contact Rating: See Chart

### Coil

Coil voltage: See Chart

Coil resistances: See Chart

### Operational Characteristics

Timing Values . . . . Operate Time: 20 mS max

Release Time: 20 mS max

### Insulation Characteristics

Dielectric strength: 500 VRMS, between Contacts and Coil

### Environmental Characteristics

Operating: -40°C to +125°C

Storage: -40°C to +155°C

### Life Expectancy

Mechanical Life: 10,000,000 operations (18,000 operations/hr)

Electrical Life: 100,000 operations (1,200 operations/hr)

### Weight

Std: 1.1 oz (31 gram) approx