


Serrated Washers




SR-Z Series serrated washers can be used in conjunction with a locknut to provide additional fixing security and aid in bonding an entry component to the equipment.

Thread Types: Metric, NPT, NPSM, ISO Pipe (BSP), PG, ET
Materials: 316 Stainless Steel, Steel/Zinc
CE Conformity: Please refer to *European Directives & CE Marking*
Part Number: Please refer to *Part Numbering System*

Dimensions of Metric and NPT Versions

Size	O/D	Thickness		Size	O/D	Thickness	
		Min	Max			Min	Max
M16	25.5	1.0	2.5	½" NPT	32.5	1.5	3.0
M20	32.5	1.5	3.0	¾" NPT	39.5	1.5	3.75
M25	39.5	1.5	3.75	1" NPT	49.5	1.5	4-5
M32	49.5	1.5	4-5	1¼" NPT	64.5	1.5	4-5
M40	64.5	1.5	4-5	1½" NPT	80.5	1.5	4-5
M50	80.5	1.5	4-5	2" NPT	100.0	1.5	4-5
M63	100.0	1.5	4-5	2½" NPT	112.0	1.5	4-5
M75	112.0	1.5	4-5	3" NPT	125.0	1.5	4-5

IP Washers



SW-Z Series IP Sealing Washers are fitted between an entry component and the equipment to maintain the ingress protection of the equipment.

Thread Types: Metric, NPT, NPSM, ISO Pipe (BSP), PG, ET
Materials: Nylon 6, Red Fibre, PTFE, (PTFE), Neoprene
CE Conformity: Please refer to *European Directives & CE Marking*
Part Number: Please refer to *Part Numbering System*

Dimensions of Metric and NPT Versions (Nylon 6 & Red Fibre)

Size	O/D	Thickness		Size	O/D	Thickness	
		Min	Max			Min	Max
M16	26.0	1.5		½" NPT	32.0	1.5	
M20	30.5	1.5		¾" NPT	38.5	1.5	
M25	38.0	1.5		1" NPT	45.0	1.5	
M32	42.6	1.5		1¼" NPT	55.5	1.5	
M40	56.0	1.5		1½" NPT	65.0	1.5	
M50	64.0	1.5		2" NPT	79.0	1.5	
M63	78.0	1.5		2½" NPT	90.0	1.5	
M75	90.0	1.5		3" NPT	116.0	1.5	