

Farnell Electronic Components Limited

Marketing & Purchasing Centre

Armley Road
Leeds LS12 2QQ
West Yorkshire

Phone (0532) 790101 (25 lines)
Dateline 310160
Telex 556000
Fax (0532) 633404

THIS DATA SHEET COVERS
THE FOLLOWING PART NOS
106-312/313
106-328 TO 332
150-369 to 391.

* CORDAGE AND LEADS/CORDS

{ FEC Nos; 106-312 to 106-313
{ FEC Nos; 106-328 to 106-332

PHYSICAL CHARACTERISTICS

CONDUCTOR ; 26 AWG 7 STRAND COPPER
INSULATION ; PVC
JACKET ; PVC

PERFORMANCE

CONDUCTOR RESISTANCE > 20 MILLIOHMS PER METER
INSULATION RESISTANCE > 100 M OHM
DIELECTRIC STRENGTH > 500 VAC

MECHANICAL


PLUG PULL FORCE ; 18 LBS MIN
TERMINAL CRIMPING STRENGTH ; 4.4 LBS MIN

LINE CORD FLAT

	1	2	3	4	5	6	7	8
4 WAY WHITE SHEATHED ISO-369			BLACK	RED	GREEN	YELLOW		
6 " " " ISO-370		WHITE	"	"	"	"	BLUE	
* 8 " BLACK " ISO-371	BLUE	ORANGE	"	"	"	"	BROWN	GREEN

LINE CORDS - PLUG TO SPADE

4 WAY IVORY SHEATHED 106-328			BLACK	RED	GREEN	YELLOW		
" " BLACK " 106-329			"	"	"	"		
6 " IVORY " 106-330		WHITE	"	"	"	"	BLUE	
" " BLACK " 106-331		"	"	"	"	"	"	
8 " BLACK " 106-332	BLUE	ORANGE	"	"	"	"	BROWN	WHITE



With Compliments