



NOTES:

1. MATERIAL -
PHOSPHOR BRONZE CDA 521
THICKNESS: $(0.200) \pm 0.008$
TENSILE STRENGTH: 655-760 N/mm²
PLATING - SEE SHEET 2
2. FOR DIMENSIONS A, B, C, D, F & G
SEE SHEET 2
3. FOR WIRE SIZE & INSULATION DIA
SEE SHEET 2
4. THIS TERMINAL TO MATE WITH
 $(0.635) \pm 0.025$ SQUARE PIN
5. MAX BURR AFTER CUT-OFF
 $(0.025) \pm 0.001$

REMOVED LEAD REF. EC NO. E2006-0155 DRAWN: JDENNEHY 2005/08/29 CHKD: DMORIARTY 2005/08/29 APPR: JDENNEHY 2005/09/05	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 10:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		mm	INCH	DRAWN BY NPC	DATE 1987/08/27	TITLE C-GRID III FEMALE CRIMP TERMINAL			
		4 PLACES ± ---	± ---	CHECKED BY D.MORIARTY	DATE 2005/08/26	MOLEX INCORPORATED			
		3 PLACES ± ---	± 0.004	APPROVED BY JDENNEHY	DATE 2005/08/26				
		2 PLACES ± 0.1	± 0.008	MATERIAL NO. SD-90119		DOCUMENT NO. SD-90119		SHEET NO. 1 OF 2	
		1 PLACE ± 0.2	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					
		ANGULAR ± 5°		SEE CHART					
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

PPL PLA LD 0 D P N

	Λ
0 0	Ε
0	Γ
0 20	Λ
0 2	Ε
0 22	Γ
2 09	Λ
2 0	Ε
2	Γ
2 20	Λ
2 2	Ε
	Γ

