



NOTE: All relevant materials are complied with RoHS directive .

| | | | |
|-----|---|-------|----------|
| 8 | PLASTO-VISCO-ELASTIC BODY | 4 | M582 |
| 7 | SCREW 3*6PMB | 4 | M805 |
| 6 | METAL CASE, THICKNESS 0.8mm | 1set | M415 |
| | UL1061 26AWG INSULATOR, LENGTH 200mm | 149 | M541 |
| 5 | MAIN HEART 9-27-4 | 1 | M94 |
| | SCREW 4*12.5mm WITH PAD | 1set | M94 |
| | KNOB FOR A, B, C, D, SWITCH | 1 | M94 |
| 4 | HEX-NUT WITH SCREW CAP 3*6mm | 2Dset | M95 |
| 3 | HEX-NUT 4.75*13mm, SCREW CAP 4.75*1.5mm | 10set | M95 |
| 2 | MINI DIN6 FEMALE, GOLD FLASH ON CONTACTS, BLACK INSULATOR | 10 | M367 |
| 1 | HD15 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR | 5 | M108 |
| No. | DESCRIPTION | QTY | Supplier |

| | | | |
|----------|------|----------|--------|
| APPROVED | | | |
| CHECKED | RAN | | |
| DRAWING | TIAN | ITEM NO. | SB-704 |

