

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	4V/40V/400V/600V	$\pm(0.8\%+1)$
AC Voltage	4V/40V/400V/600V	$\pm(1.2\%+5)$
AC Current	40A/400A	$\pm(1.5\%+5)$
Resistance	400 $\Omega$ /4k $\Omega$ /40k $\Omega$ /400k $\Omega$ /4M $\Omega$ /40M $\Omega$	$\pm(1\%+2)$
Frequency	400Hz	$\pm(1\%+3)$
Duty Cycle	99.90%	✓
<b>Special Functions</b>		
Auto Function		✓
Data Hold		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10M $\Omega$	✓
Max. Display	3999	✓

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	40 x 37 mm
Product Colour	Red and Grey
Product Net Weight	352g
Product Size	210 x 53 x 27mm
Standard Accessories	Test Lead, English Manual, Carrying Bag
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	510 x 490 x 330mm (0.082 CBM Per Standard Carton)
Standard Carton Gross Weight	21kg