Technical Data

Issue 11 / May 2006

AT74 High Temperature PVC Electrical Insulation Tape

NOTE

General description

A PVC film coated with a pressure sensitive adhesive.

- Flame retardant
- Self-extinguishing
- Good high temperature performance
- Flexible
- Conformable to awkward shapes
- Good abrasion resistance
- Good resistance to ageing
- UV resistant
- Non-corrosive adhesive
- Easy unwind
- Water resistant

Specification

Certification* to the following standards may be available on request, BS3887 : 1991 and BS EN 60454-3-1/ Type 10 (Formerly BS 3924, VDE 0310/DIN 40633).

Technical Details

Typical values		
Thickness	0.15mm	
Breaking Load	25 N/cm	
Elongation	150%	
Adhesion		
Steel	3.0 N/cm	
Self	2.6 N/cm	
Water Extract		
рН	6.5 to 7.5	
Conductivity	Max. 2 mS/m	
Breakdown Voltage	9.5 kV	
Copper Corrosion	No Staining	
Flame Retardancy	Self extinguishing	
RoHS Compliant	Yes	
Service Temperature	-5°C to +105°C	
Storage Temperature	+12°C to +25°C	

*Standard charge for certificate: £25.00.



the right to improve products and any change in specification
will result in a re-issue of the relevant 'Technical Data Sheet'.
Customers should satisfy themselves that the tape is suitable
for their requirements whether after such modifications or
otherwise. Please check that you have the latest issue of the
'Technical Data Sheet'. All slitting and length tolerances are to
British Standards. Before use the customer is advised to con-
sult the Health & Safety Data Sheet produced by the company
for this product, which is available on request.
STORAGE
Tapes stored below the minimum recommended temperature
will require warming up to that level before use. Up to 24
hours may be required for this to take place.
nours may be required for this to take place.

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINI-MUM values for specification purposes. The Company reserves





AFERA Association des Fabricants Européens de Rubans Auto-Adhésifs.

Advance Tapes International Limited, PO Box 122, Abbey Meadows, Leicester, LE4 5RA. Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com