





Led Signalleuchten Einbaudurchmesser 6 mm
Led Indicators Body diameter 6 mm

Innenreflektor
Interior reflector

| Bestell-Nr. | Farbe | $V_{OP} +10\%$ (V) | $I_{OP max.}$ (mA) | V_F (V) | $I_{V typ}$ (mcd) $*I_F = 20mA$ | $I_{F max.}$ (mA) | Abb. | Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No. | 19030-A | A | |
|-------------|------------------------|-----------------------|-----------------------|--------------|------------------------------------|----------------------|-------|---|---|---|---------|
| Part No. | Colour | (V) | (mA) | (V) | $*I_F = 20mA$ | (mA) | Illu. | | | | |
| 1903*000 | Rot Red | | | 1,6/2,0 | *4,0 | 75 | A |  | | | |
| 1903*001 | Grün Green | | | 2,0/2,6 | *34,0 | 45 | A | | | | |
| 1903*002 | Gelb Yellow | | | 2,0/2,6 | *28,0 | 45 | A | | | | |
| 1903*003 | Super rot Super red | | | 2,0/2,6 | *15,0 | 45 | A | | | | |
| 1903*050 | Rot Red | | | 1,6/2,0 | *4,0 | 75 | B | |  | | |
| 1903*051 | Grün Green | | | 2,0/2,6 | *34,0 | 45 | B | | | | |
| 1903*052 | Gelb Yellow | | | 2,0/2,6 | *28,0 | 45 | B | | | | |
| 1903*053 | Super rot Super red | | | 2,0/2,6 | *15,0 | 45 | B | | | | |
| 1903*150 | Rot Red | 6 | 30 | | 4,5 | | B | | | | |
| 1903*151 | Grün Green | 6 | 30 | | 50,0 | | B | | | Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No. | 19030-B |
| 1903*152 | Gelb Yellow | 6 | 30 | | 42,0 | | B | | | | |
| 1903*153 | Super rot Super red | 6 | 30 | | 22,0 | | B |  | | | |
| 1903*250 | Rot Red | 12 | 30 | | 4,5 | | B | | | | |
| 1903*251 | Grün Green | 12 | 30 | | 50,0 | | B | | | | |
| 1903*252 | Gelb Yellow | 12 | 30 | | 42,0 | | B | | | | |
| 1903*253 | Super rot Super red | 12 | 30 | | 22,0 | | B | | | | |
| 1903*350 | Rot Red | 24 | 18 | | 4,0 | | B | |  | | |
| 1903*351 | Grün Green | 24 | 18 | | 31,0 | | B | | | | |
| 1903*352 | Gelb Yellow | 24 | 18 | | 25,0 | | B | | | | |
| 1903*353 | Super rot Super red | 24 | 18 | | 14,5 | | B | | | | |

Blaue Led Signalleuchten lieferbar.

Bei Bestellung bitte an die letzte Stelle der jeweiligen Bestellnummer die "7" einsetzen.

Arbeitstemperatur (T_{OP}): -55°C - +70°C
 Lagertemperatur (T_{STG}): -55°C - +100°C

* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0 Schwarzchrom = 1

Beispiel: 19030000 rot mit Glanzchrom
 19031000 rot mit Schwarzchrom

Led Signalleuchten mit anderen Spannungen auf Anfrage

Technische Änderungen vorbehalten

Blue Led Indicators can be supplied.

When ordering, please use on the relevant partnumber the "7" for the last digit.

Operating temperature (T_{OP}): -55°C - +70°C
 Storage temperature (T_{STG}): -55°C - +100°C

* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0 Black chrome = 1

Example: 19030000 red with bright chrome
 19031000 red with black chrome

Led Indicators with other voltages upon request

Specification subject to change without notice