

Loctite 243

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

SDS no.: 153494

V001.3 Revision: 08.01.2008

printing date: 29.01.2008

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

Loctite 243

Intended use:

Anaerobic

Company name:

Henkel Limited Technologies House Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (0)1442 278000 Fax-no.: +44 (0)1442 278071

E-mail address of person responsible for Safety Data Sheet:

ua-products a fety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44(0)8701906777

2. Hazards identification

Prolonged contact with skin, particularly damaged skin, may cause sensitization or dermatitis in sensitive individuals. The product is not hazardous within the meaning of the valid (EU) preparation guideline.

3. Composition / information on ingredients

General chemical description:

Anaerobic thread sealant

Declaration of ingredients according to EC/1907/2006:

Hazardous components	EINECS	content	Classification	
CAS-No.	ELINCS			
Cumene hydroperoxide	201-254-7	> 0,1 - < 1 %	O - Oxidizing; R7	
80-15-9			T - Toxic; R23	
			Xn - Harmful; R21/22, R48/20/22	
			C - Corrosive; R34	
			N - Dangerous for the environment; R51, R53	
Cumene	202-704-5	> 0,1 -< 0,3 %	R10	
98-82-8			Xn - Harmful; R65	
			Xi - Irritant; R37	
			N - Dangerous for the environment; R51, R53	

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

MSDS-No.: 153494 Loctite 243 Page 2 of 5

V001.3

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestions

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:

Oxides of carbon, oxides of nitrogen, irritating organic vapors., Sulphur oxides

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. Handling and storage

Handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation

Storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

MSDS-No.: 153494 Loctite 243 Page 3 of 5

V001.3

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m ³	Туре	Category	Remarks
CUMENE 98-82-8	20	100	Time Weighted Average (TWA).		EU-2000/39/EC
CUMENE 98-82-8	50	250	Short Term Exposure Limit (STEL):		EU-2000/39/EC
CUMENE 98-82-8			Skin designation.	Can be absorbed through the skin.	EU-2000/39/EC
CUMENE 98-82-8	25	125	Time Weighted Average (TWA).		EH40 WEL
CUMENE 98-82-8	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
CUMENE 98-82-8			Skin designation.	Can be absorbed through the skin.	EH40 WEL

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed

9. Physical and chemical properties

General characteristics:

Appearance liquid blue

Odor: characteristic

Phys./chem. properties:

pH-value not applicable Boiling point $> 149 \,^{\circ}\text{C} (> 300.2 \,^{\circ}\text{F})$ Flash point $> 93 \,^{\circ}\text{C} (> 199.4 \,^{\circ}\text{F})$ Vapor pressure $0,133 \,^{\circ}\text{mbar}$

(27,0 °C (80.6 °F))

Density 1,08 g/cm³

(20 °C (68 °F))
Solubility (qualitative)
Slight

(Solvent: Water)

VOC content < 2,00 % (1999/13/EC)

MSDS-No.: 153494 Loctite 243 Page 4 of 5

V001.3

10. Stability and reactivity

Conditions to avoid:

Stable

Materials to avoid:

Reaction with strong acids.

Reacts with strong oxidants.

11. Toxicological information

Oral toxicity:

This material is considered to have low toxicity if swallowed.

May cause irritation to the digestive tract.

Inhalative toxicity:

Due to the low volatility of the product there are no hazards associated with inhalation under normal conditions of use

Skin irritation:

Although it is not a common sensitizer there may be a risk of sensitization on prolonged or repeated contact with damaged

Eye irritation:

May cause mild irritation to the eyes.

12. Ecological information

Mobility:

Cured adhesives are immobile.

General ecological information:

Do not empty into drains / surface water / ground water.

13. Disposal considerations

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Waste code(EWC):

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Risk phrases:

Not classified as hazardous.

MSDS-No.: 153494 Loctite 243 Page 5 of 5

V001.3

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicted by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R37 Irritating to respiratory system.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.