





- NOTES
- Δ 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
 - Δ 2 HARDWARE FURNISHED UNASSEMBLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE ----- 9-13 OZ	CONTACT ARRANGEMENT S P D T	DO NOT SCALE PRINT
RELEASE FORCE ----- 4 OZ MIN	UNDERWRITERS' LAB. INC. LISTED RATING	UNLESS OTHERWISE NOTED
DIFFERENTIAL TRAVEL --- .0004-.0020	-L96- 15 A-125, 250, OR 480 VAC	DIMENSIONS ARE IN INCHES
OVERTRAVEL ----- .219 MIN	1/2 A-125 VDC; 1/4 A-250 VDC	TOLERANCES ARE:
	1/8 HP-125 VAC; 1/4 HP-250 VAC	ONE PLACE (.0) ±.030
	-L288-   	TWO PLACE (.00) ±.015
	-L299- 16A 250V  T85 5E4	THREE PLACE (.000) ±.005
	-L306-	ANGLES
		WEIGHT .105 LB

BZ-2RQ1-P4
 PAGE 1 OF 1
M
 DRAWING NUMBER
9
 ISSUE
 REVISIONS
 A CO17410
 RJW
 15 AUG 64
 B CO58594
 KEW
 18 MAR 86
 C CO-73287-G
 JAL
 20 OCT 93
 D CO-75367B
 L J F
 3 MAR 94
 E CO-77863
 G J W
 6 MAY 96
 F CO-82133
 CSL
 30 JUL 96
 G CO93346
 D L T
 10 SEP 98
 CHECK
 14 SEPT 64
 DRAW
 15 AUG 64
 FORMTEK
 FC-30376