



**Euro-connector-block 4 mm<sup>2</sup>, divisible  
1 - 12-poles, raised base,  
also with wire-protection (DS, DSS)**

Assembly-bore : Ø 3,5 mm  
Casing : natural polyamide  
Insert : zinc-plated steel  
Screw : M 3 nickel-plated steel  
Wire-protection : chrome-nickel-steel

This connector is available from 1 - 12-poles or can be cut according to your requirements. Delivery will be effected ready for installation with slightly twisted screws, which are protected against self-loosening in the insulation-part. Also available with glow wire resistance 750°C, flame < 2 sec. (IEC/EN60335-1).






Accessories as description-labels and components are available.



**32A  
450V**

PTI 250

T110



No. of poles	Length	Article-no.	kg/100 pcs.	Article-no. with DS	kg/100 pcs.	Article-no. with DSS	kg/100 pcs.	Article-no. with MB	kg/100 pcs.	Pkg. qty.
1	7,0	1012950001	0,3	1012952001	0,3	1012953001	0,3	1012956001	0,3	1000
2	17,0	1012950002	0,6	1012952002	0,6	1012953002	0,6	1012956002	0,6	1000
3	27,0	1012950003	0,86	1012952003	0,86	1012953003	0,86	1012956003	0,86	500
4	37,0	1012950004	1,12	1012952004	1,12	1012953004	1,12	1012956004	1,12	500
5	47,0	1012950005	1,43	1012952005	1,43	1012953005	1,43	1012956005	1,43	250
6	57,0	1012950006	1,75	1012952006	1,75	1012953006	1,75	1012956006	1,75	250
7	67,0	1012950007	2,06	1012952007	2,06	1012953007	2,06	1012956007	2,06	100
8	77,0	1012950008	2,31	1012952008	2,31	1012953008	2,31	1012956008	2,31	100
9	87,0	1012950009	2,57	1012952009	2,57	1012953009	2,57	1012956009	2,57	100
10	97,0	1012950010	2,88	1012952010	2,88	1012953010	2,88	1012956010	2,88	100
11	107,0	1012950011	3,18	1012952011	3,18	1012953011	3,18	1012956011	3,18	100
12	117,0	1012950012	3,5	1012952012	3,5	1012953012	3,5	1012956012	3,5	100

