

DATA SHEET

STONTRONICS


THE POWER TO SUPPLY

PART NO: T 2400AD

ISSUE NO: 1

CUSTOMER: CPC / FARNELL

RoHS



CUSTOMER NO: PW00812 / 4266330

DESCRIPTION 100-240Vac:15Vdc Reg. 700mA Wall Mount PSU



INPUT VOLTS	100-240Vac
FREQUENCY	50-60Hz
INPUT CURRENT (min.)	100mA max
INPUT CURRENT (max.)	380mA RMS
LEAKAGE CURRENT	0.25mA
EFFICIENCY (min)	70%
O/P VOLTS NO LOAD	15Vdc
O/P VOLTS (+/-5%)	15Vdc
O/P CURRENT	700mA
OVER VOLTAGE (Shut Down)	17 to 19Vdc
SHORT CIRCUIT (Shut Down & Auto Restart)	
RIPPLE & NOISE (P-P)	120mV
OPERATING TEMPERATURE (°C)	0 to 40
HUMIDITY	20 to 80%
STORAGE TEMPERATURE (°C)	-10 to 70
HUMIDITY	10 to 90%
FLASH TEST (Input to Output)	3KVac
INPUT CONNECTOR	2 Pin Euro
LEAD LENGTH	2 mtr.
OUPUT CONNECTOR	2.1x5.5x12mm
OUTPUT POLARITY	N/A
LEAD LENGTH	1.8 mtr.
LENGTH	91mm
WIDTH	68mm
DEPTH	53.5mm
MOUNTING CENTRES	105mm
WEIGHT	200gm
CASE MATERIAL	UL94-V0

LABELLING:

STONTRONICS LIMITED 
www.stontronics.co.uk
T2400AD 
 I/P - 100V-240VAC 50-60Hz
 O/P - 15 VDC @ 700mA
PW00812 

STONTRONICS LIMITED 
www.stontronics.co.uk
T2400AD 
 I/P :100V-240VAC 50/60Hz
 O/P : 15.0 VDC @ 700mA
 CAUTION: LIVE PARTS ENCLOSED 

SCHEMATIC

