



TECHNICAL SPECIFICATION

Technical Service Department,
Spill Safety, Worsham Mill, Minster Lovell,
Oxford, OX29 0TA
Tel.: 01993 824000
Fax: 01993 824422

Chemical Adsorbent Pads

Pad Conformity:

All are tested in accordance with BS7959 part 1

Pad Performance:

A quick response chemical adsorbent spill pad that can be used inside or outside.

JSP would expect that in normal conditions 1 of each of the products will adsorb the following:

Size (Metres)	Capacity (Litres)
0.48 x 0.43	0.8

Pad Materials:

Melt Blown Polypropylene. (Colour – Yellow)

Size & Weight:

0.43x0.45x0.59M

8Kg (approx based on 100 pack quantity)



Use:

Before entering hazard are, be sure to wear the appropriate personal protective equipment for the substance spilled.

Deploy the pads as required to contain and soak up the spillage.

Disposal:

Put all used product into a non perforated bag and seal. Dispose of all contaminated product in accordance with local regulations for the liquid involved.

Handling & Storage:

No special handling is required.

It is recommended that this product is kept dry at an ambient temperature in storage.

Limitations Of Use:

Melt Blown Polypropylene is not suitable for use in areas where strong organic peroxides or concentrated acids at 60°C or above are used. If in doubt, advice should be sought before use.