



1 Form A Solid-State Relay



i179041-2



FEATURES

- Extremely low operating current
- High speed operation
- Isolation test voltage 5300 V_{RMS}
- Current limit protection
- High surge capability
- DC only option
- Clean bounce free switching
- Low power consumption
- Surface mountable
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT

DESCRIPTION

The LH1525 relay are SPST normally open switches (1 form A) that can replace electromechanical relays in many applications. The relay requires a minimal amount of LED drive current to operate, making it ideal for battery powered and power consumption sensitive applications. The relay is constructed using a GaAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology, comprised of a photodiode array, switch-control circuitry, and MOSFET switches. In addition, the relay employs current-limiting circuitry, enabling it to pass lightning surge testing as per ANSI/TIA-968-B and other regulatory surge requirements when overvoltage protection is provided. The relay can be configured for AC/DC or DC-only operation.

APPLICATIONS

- General telecom switching
- Battery powered switch applications
- Industrial controls
- Programmable controllers
- Instrumentation

Note

- See "solid-state relays" (application note 56)

AGENCY APPROVALS

UL1577: file no. E52744 system code H, double protection
 CSA: certification 093751
 BSI: no. 7979/7980
 FIMKO: 25419

| ORDERING INFORMATION | | | | | | | | | | | | | |
|----------------------|---|---|---|---|---|----------------------------|---|---|-----------------|---|--------------------|---------------------|--|
| L | H | 1 | 5 | 2 | 5 | # | # | # | T | R | DIP 7.62 mm | SMD > 0.1 mm | |
| PART NUMBER | | | | | | ELECTR. VARIATION | | | PACKAGE CONFIG. | | | TAPE AND REEL | |
| PACKAGE | | | | | | UL, CSA, BSI, FIMKO | | | | | | | |
| SMD-6, tubes | | | | | | LH1525AAB | | | | | | | |
| SMD-6, tape and reel | | | | | | LH1525AABTR | | | | | | | |
| DIP-6, tubes | | | | | | LH1525AT | | | | | | | |



| ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | |
|--|----------------------------------|------------|---------------|--------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| INPUT | | | | |
| LED input ratings: continuous forward current | | I_F | 50 | mA |
| LED input ratings: reverse voltage | | V_R | 8 | V |
| OUTPUT | | | | |
| Output operation (each channel): DC or peak AC load voltage | $I_L \leq 50\text{ }\mu\text{A}$ | V_L | 400 | V |
| Continuous DC load current, bidirectional operation pin 4 to 6 | | I_L | 125 | mA |
| Continuous DC load current, unidirectional operation pins 4, 6 (+) to pin 5 (-) | | I_L | 250 | mA |
| SSR | | | | |
| Ambient operating temperature range | | T_{amb} | - 40 to + 85 | $^{\circ}\text{C}$ |
| Storage temperature range | | T_{stg} | - 40 to + 150 | $^{\circ}\text{C}$ |
| Pin soldering temperature ⁽¹⁾ | $t = 10\text{ s max.}$ | T_{sld} | 260 | $^{\circ}\text{C}$ |
| Input to output isolation test voltage | $t = 1\text{ s}$ | V_{ISO} | 5300 | V_{RMS} |
| Power dissipation | | P_{diss} | 550 | mW |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- ⁽¹⁾ Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|------------|-------|-------|------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | |
| LED forward current, switch turn-on | $I_L = 100\text{ mA}$, $t = 10\text{ ms}$ | I_{Fon} | | 0.33 | 0.5 | mA |
| LED forward current, switch turn-off | $V_L = \pm 350\text{ V}$, $t = 100\text{ ms}$ | I_{Foff} | 0.001 | 0.23 | | mA |
| LED forward voltage | $I_F = 1.5\text{ mA}$ | V_F | 0.8 | 1.16 | 1.40 | V |
| OUTPUT | | | | | | |
| On-resistance, AC/DC, each pole | $I_F = 1.5\text{ mA}$, $I_L = \pm 50\text{ mA}$ | R_{ON} | 17 | 26 | 36 | Ω |
| On-resistance, DC: pin 4, 6 (+) to 5 (-) | $I_F = 1.5\text{ mA}$, $I_L = 100\text{ mA}$ | R_{ON} | 4.25 | 7 | 8.25 | Ω |
| Off-resistance | $I_F = 0\text{ mA}$, $V_L = \pm 100\text{ V}$ | R_{OFF} | | 2000 | | $\text{G}\Omega$ |
| Current limit AC ⁽¹⁾ : pin 4 (\pm) to 6 (\pm) | $I_F = 1.5\text{ mA}$, $t = 5\text{ ms}$, $V_L = 7\text{ V}$ | I_{LMT} | 170 | 185 | 270 | mA |
| Off-state leakage current | $I_F = 0\text{ mA}$, $V_L = \pm 100\text{ V}$ | I_O | | 0.67 | 200 | nA |
| | $I_F = 0\text{ mA}$, $V_L = \pm 400\text{ V}$ | I_O | | 0.096 | 1 | μA |
| Output capacitance | $I_F = 0\text{ mA}$, $V_L = 1\text{ V}$ | C_O | | 22 | | pF |
| | $I_F = 0\text{ mA}$, $V_L = 50\text{ V}$ | C_O | | 6.42 | | pF |
| Switch offset | $I_F = 5\text{ mA}$ | V_{OS} | | 0.2 | | μV |
| TRANSFER | | | | | | |
| Capacitance (input to output) | $V_{ISO} = 1\text{ V}$ | C_{IO} | | 0.75 | | pF |

Notes

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.
- ⁽¹⁾ No DC mode current limit available.

| SWITCHING CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|---|--|-----------|------|------|------|------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Turn-on time | $I_F = 1.5\text{ mA}$, $I_L = 50\text{ mA}$ | t_{on} | | 1.25 | | ms |
| | $I_F = 5\text{ mA}$, $I_L = 50\text{ mA}$ | t_{on} | | 0.22 | 1 | ms |
| Turn-off time | $I_F = 1.5\text{ mA}$, $I_L = 50\text{ mA}$ | t_{off} | | 0.6 | | ms |
| | $I_F = 5\text{ mA}$, $I_L = 50\text{ mA}$ | t_{off} | | 1.1 | 1.5 | ms |



| SAFETY AND INSULATION RATINGS | | | | |
|---|--|------------|----------------|------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| Climatic classification | IEC 68 part 1 | | 40/85/21 | |
| Pollution degree | DIN VDE 0109 | | 2 | |
| Tracking resistance (comparative tracking index) | Insulation group IIIa | CTI | 175 | |
| Highest allowable overvoltage | Transient overvoltage | V_{IOTM} | 8000 | V_{peak} |
| Max. working insulation voltage | Recurring peak voltage | V_{IORM} | 890 | V_{peak} |
| Insulation resistance at 25 °C | $V_{IO} = 500 V$ | R_{IS} | $\geq 10^{12}$ | Ω |
| Insulation resistance at T_S | | R_{IS} | $\geq 10^9$ | Ω |
| Insulation resistance at 100 °C | | R_{IS} | $\geq 10^{11}$ | Ω |
| Partial discharge test voltage | Method e a, $V_{pd} = V_{IORM} \times 1.875$ | V_{pd} | 1669 | V_{peak} |
| Safety limiting values - maximum values allowed in the event of a failure | Case temperature | T_{SI} | 175 | °C |
| | Input current | I_{SI} | 300 | mA |
| | Output power | P_{SO} | 700 | mW |
| Minimum external air gap (clearance) | Measured from input terminals to output terminals, shortest distance through air | | ≥ 7 | mm |
| Minimum external tracking (creepage) | Measured from input terminals to output terminals, shortest distance path along body | | ≥ 7 | mm |

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ °C}$, unless otherwise specified)




Fig. 1 - Recommended Operating Conditions




Fig. 3 - LED Forward Current vs. Forward Voltage




Fig. 2 - LED Voltage vs. Temperature




Fig. 4 - LED Reverse Current vs. LED Reverse Voltage






Fig. 5 - LED Current for Switch Turn-on vs. Temperature




ih1525at_07

Fig. 8 - Load Current vs. Load Voltage




ih1525at_05

Fig. 6 - On-Resistance vs. Temperature




ih1525at_08

Fig. 9 - Current Limit vs. Temperature




ih1525at_06

Fig. 7 - LED Dropout Voltage vs. Temperature




ih1525at_09

Fig. 10 - Variation in On-resistance vs. LED Current




ilh1525at_10

Fig. 11 - Switch Capacitance vs. Applied Voltage




ilh1525at_13

Fig. 14 - Insertion Loss vs. Frequency




ilh1525at_11

Fig. 12 - Output Isolation




ilh1525at_14

Fig. 15 - Switch Breakdown Voltage vs. Load Current



ilh1525at_12

Fig. 13 - Leakage Current vs. Applied Voltage at Elevated Temperatures



ilh1525at_15

Fig. 16 - Switch Breakdown Voltage vs. Temperature




Fig. 17 - Switch Offset Voltage vs. Temperature




Fig. 20 - Turn-off Time vs. Temperature




Fig. 18 - LED Offset Voltage vs. LED Current




Fig. 21 - Turn-on Time vs. LED Temperature




Fig. 19 - Turn-on Time vs. LED Current




Fig. 22 - Turn-off Time vs. LED Current



APPLICATIONS


INPUT CONTROL

The LH1525 low turn-on current SSR has highly sensitive photodetection circuits that will detect even the most minute currents flowing through the LED. Leakage current must be considered when designing a circuit to turn on and off these relays.

Figure 23 shows a typical logic circuit for providing LED drive current. R_1 is the input resistor that limits the amount of current flowing through the LED. For 5 V operation, a 2700 Ω resistor will limit the drive current to about 1.4 mA. Where high-speed actuation is desirable, use a lower value resistor for R_1 . An additional RC peaking circuit is not required with the LH1525 relay.

R_2 is an optional pull-up resistor which pulls the logic level high output (V_{OH}) up toward the V_S potential. The pull-up resistance is set at a high value to minimize the overall current drawn from the V_S . The primary purpose of this resistor is to keep the differential voltage across the LED below its turn-on threshold. LED dropout voltage is graphed vs. temperature in the typical performance characteristics section. When the logic gate is high, leakage current will flow through R_2 . R_2 will draw up to 8 mA before developing a


voltage potential which may possibly turn on the LED. Each application should be evaluated, over the full operating temperature range to make sure that leakage current through the input control LED is kept to a value less than the minimum LED forward current for switch turn-off specification.




ilh1525at_22

Fig. 23 - Input Control Circuit


PACKAGE DIMENSIONS in millimeters



i178001



PACKAGE MARKING



Note

- Tape and reel suffix (TR) is not part of the package marking.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.