

DWTC Series

Heat Shrink Tubing

PRO-POWER
Quality Cables



Features:

- Excellent mechanical strength.
- Excellent abrasion resistance.
- Excellent optical clarity.
- Environmental sealing.
- Shrink ratio 4:1.



It is a flexible, heat-shrinkable, dual-wall tubing with an integrally bonded meltable adhesive inner liner designed to offer moisture proof encapsulation to a wide variety of substrates. Available in clear, DWTC offers excellent clarity for protection of substrates that may need to be inspected during service. The tough outer jacket gives excellent mechanical strength with a high resistance to splitting. The high shrinkage ratio means that only four sizes are needed to give protection to a full range of irregular shapes with widely varying dimensions.

Performance

Test	Test Method	Test Requirement
Minimum Inner Wall Adhesion DWTC to Aluminium	-	60N/25mm
Heat Shock	4 Hours at 200°C	Pass-no Dripping, Cracking or Flowing of Outer Wall
Heat Ageing	168 Hours at 120°C	
Low Temperature Flexibility	4 Hours at -55°C	Pass-no Cracking
Fluid Resistance	24 Hours at 23°C, ISO 37	Minimum Tensile Strength : 15MPa Minimum Ultimate Elongation : 200%
	Test Fluids	Diesel Fuel (BS 2869 Class A1) Break Fluid (H-515) Lubricating Oil (0-149)

PRO-POWER
Quality Cables

DWTC Series

Heat Shrink Tubing

PRO-POWER
Quality Cables

Specification Table


Inside Diameter		Wall Thickness		Length (m)	Part Number
Minimum Expanded as Supplied (D)	Maximum Recovered After Heating (d)	Nominal Total Wall Recovered After Heating (W)	Nominal Meltable Wall Recovered After Heating (W1)		
4.0	1.0	0.8	0.25	1.2	DWFC-4/1-X-4FT
8.0	2.0	0.9			DWFC-8/2-X-4FT
12.0	3.0	1.2	0.40		DWFC-12/3-X-4FT

Dimensions : Millimetres (Unless Specified)

Note:

The wall thickness of the tubing will be less than specified if recovery is restricted during shrinkage.

Part Number Explanation:



Inside Diameter : Expanded as supplied/Recovered after heating.

Colour Code : X = Clear.

PRO-POWER
Quality Cables

DWTC Series

Heat Shrink Tubing

PRO-POWER
Quality Cables

Notes:

International Sales Offices:

	AUSTRALIA – Farnell InOne Tel No: ++ 61 2 9645 8888 Fax No: ++ 61 2 9644 7898		FINLAND – Farnell InOne Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411		NETHERLANDS – Farnell InOne Tel No: ++ 31 30 241 7373 Fax No: ++ 31 30 241 7333		SWITZERLAND – Farnell InOne Tel No: ++ 41 1 204 64 64 Fax No: ++ 41 1 204 64 54
	AUSTRIA – Farnell InOne Tel No: ++ 43 662 2180 680 Fax No: ++ 43 662 2180 670		FRANCE – Farnell InOne Tel No: ++ 33 474 68 99 99 Fax No: ++ 33 474 68 99 90		NEW ZEALAND – Farnell InOne Tel No: ++ 64 9 357 0646 Fax No: ++ 64 9 357 0656		UK – Farnell InOne Tel No: ++ 44 8701 200 200 Fax No: ++ 44 8701 200 201
	BELGIUM – Farnell InOne Tel No: ++ 32 3 475 2810 Fax No: ++ 32 3 227 3648		GERMANY – Farnell InOne Tel No: ++ 49 89 61 39 39 39 Fax No: ++ 49 89 613 59 01		NORWAY – Farnell InOne Tel No: ++ 45 44 53 66 66 Fax No: ++ 45 44 53 66 02		UK – BuckHickman InOne ++ 44 8450 510 150 ++ 44 8450 510 130
	BRAZIL – Farnell-Newark InOne Tel No: ++ 55 11 4066 9400 Fax No: ++ 55 11 4066 9410		HONG KONG – Farnell-Newark InOne Tel No: ++ 852 2268 9888 Fax No: ++ 852 2268 9899		PORTUGAL – Farnell InOne Tel No: ++ 34 93 475 8804 Fax No: ++ 34 93 474 5288		UK – CPC ++ 44 8701 202 530 ++ 44 8701 202 531
	CHINA – Farnell-Newark InOne Tel No: ++86 10 6238 5152 Fax No: ++86 10 6238 5022		IRELAND – Farnell InOne Tel No: ++ 353 1 830 9277 Fax No: ++ 353 1 830 9016		SINGAPORE – Farnell-Newark InOne Tel No: ++ 65 6788 0200 Fax No: ++ 65 6788 0300	 export Tel No: ++ 44 8701 200 208 Fax No: ++ 44 8701 200 209 For enquiries from all other markets	
	DENMARK – Farnell InOne Tel No: ++ 45 44 53 66 44 Fax No: ++ 45 44 53 66 06		ITALY – Farnell InOne Tel No: ++ 39 02 93 995 200 Fax No: ++ 39 02 93 995 300		SPAIN – Farnell InOne Tel No: ++ 34 93 475 8805 Fax No: ++ 34 93 474 5107		
	ESTONIA – Farnell InOne Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411		MALAYSIA – Farnell-Newark InOne Tel No: ++ 60 3 7873 8000 Fax No: ++ 60 3 7873 7000		SWEDEN – Farnell InOne Tel No: ++ 46 8 730 50 00 Fax No: ++ 46 8 83 52 62	http://www.farnellinone.com http://www.buckhickmaninone.com http://www.cpc.co.uk	

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2004.

PRO-POWER
Quality Cables