

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	±(0.8%+1)
AC Voltage	400mV/4V/40V/400V/600V	±(1.2%+5)
DC Current	40A/1000A	±(1.5%+8)
AC Current	40A/1000A	±(2%+8)
Resistance	400Ω / 4kΩ / 40kΩ / 400kΩ / 4MΩ / 40MΩ	± (1%+2)
Temperature	-40°C~1000°C -40°F~1832°F	
Frequency	4kHz/40kHz/400kHz/4MHz/40MHz	±(1%+3)
Duty Cycle	0.1%~99.9%	
<b>Special Functions</b>		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
True RMS	AC Voltage	✓
Surge Current	AC Current	✓
Peak Max/Peak Min Mode		✓
Max/Min Mode		✓
Data Hold		✓
Sleep Mode		✓
Display Backlight		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for AC Voltage Measurement	Around 10 MΩ	✓
Max. Display		4000
Analogue Bar Graph		✓

## GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (1604A or 6LF22)
LCD Size	47 x 30 mm
Product Color	Red and Grey
Product Net Weight	533g
Product Size	285 x 105 x 45 mm
Standard Accessories	Test Lead, Alkaline Battery, English Manual, Tool Box
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	5 pcs

Standard Carton Measurement	480 x 372 x 315 (0.056CBM Per Standard Carton)
<b>Standard Carton Gross Weight</b>	11 kg