•	PART NO.				REVISIONS						
💿 multicomp	E		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		2217R Series		A	RELEASED	Ramya	08/8/09	Jagan	08/8/09	G. C	27/8/09
Dimension A ±0.20 Dimension B ±0.30	<del>.</del>	Dimension	5 5 0 ±0.30						Ro Co	<b>HS</b> mpliant	
Dimension A ±0.10 + 2.54 ±0.05 + $+$ $+$ $+$ $+$ $+$ $+$ $+$ $+$ $+$	00 ±0.05										

Dimensions: Millimetres

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:						
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information abased on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE	Ramya	08/08/09			.54mm Header - R	der - R/A, Square Pin		
	SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	CHECKED BY:	DATE:	SIZE DWG NO.			ELECTRONIC FILE		REV
		Jagan	08/08/09			M10002294		1675773-1675780_DWG	
		APPROVED BY:	DATE:						
or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Farnell plc 2008.	jury resulting from its negligence.		27/08/09	SCALE: NTS		U.O.M.: mm		SHEET: 1 OF	F 3

	PART NO.		REVISIONS										
		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE			
		-	A	RELEASED	Ramya	08/8/09	Jagan	08/8/09	G. C	27/8/09			

## Specifications:

Current rating	: 3.0A ac, dc.
Voltage rating	: 250V ac, dc.
Maximum contact resistance	: 20mΩ.
Minimum insulation resistance	: 1000MΩ.
Withstanding voltage	: 1000V ac/minute.
Operating temperature range	: -40°C to +105°C.
Material and finish:	
Insulator	: Nylon 66.
Insulator colour	: Dark white.
Contact	: Brass.
Plating	: Tin plated.

## Specification Table


Description	Circuits	Dime	nsion	Part Number
Description	Circuits	Α	В	Fait Number
Header, R/A, Square Pin, 2.54mm, 2 Way	02	2.54	5.08	2217R-02-WH2
Header, R/A, Square Pin, 2.54mm, 3 Way	03	5.08	7.62	2217R-03-WH2
Header, R/A, Square Pin, 2.54mm, 4 Way	04	7.62	10.16	2217R-04-WH2
Header, R/A, Square Pin, 2.54mm, 5 Way	05	10.16	12.70	2217R-05-WH2
Header, R/A, Square Pin, 2.54mm, 6 Way	06	12.70	15.24	2217R-06-WH2
Header, R/A, Square Pin, 2.54mm, 8 Way	08	17.78	20.32	2217R-08-WH2
Header, R/A, Square Pin, 2.54mm, 10 Way	10	22.86	25.40	2217R-10-WH2
Header, R/A, Square Pin, 2.54mm, 12 Way	12	27.94	30.48	2217R-12-WH2

Dimensions: Millimetres

(the Group ) or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:			
believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE	Ramya	08/08/09		2.54mm Header - R/A, Square Pi		
	SPECIFIED,	CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV
	DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Jagan	08/08/09	Δ	M10002294	1675773-1675780_DWG	Α
		APPROVED BY:	DATE:		I		L
or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Famell plc 2008.	Sesionity of such loss of carriage ansing) is excluded. This will not operate to immute the second s		27/08/09	SCALE: NTS	U.O.M.: mm	SHEET: 2 OF	F 3

	PART NO.			REVISIONS						
		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Ramya	08/8/09	Jagan	08/8/09	G. C	27/8/09

## Part Number Explanation:



Number of Contacts : 02 = 2, 03 = 3, 04 = 4, 05 = 5, 06 = 6, 08 = 8, 10 and 12 Contacts.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

(the Group) for are indensed to it, No licence is granied for the base of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or ornision from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or ornited. Liability for loss or damage resulting from any relance on the Information or	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:			
	UNLESS OTHERWISE	Ramya	08/08/09	] 2.8	A, Square Pin		
	SPECIFIED,	CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV
	DIMENSIONS ARE	Jagan	08/08/09	Δ	M10002294	1675773-1675780_DWG	Α
	PURPOSES ONLY	APPROVED BY:	DATE:		I		
or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Farnell plc 200	or personal injury resulting from its negligence.		27/08/09	SCALE: NTS	U.O.M.: mm	SHEET: 3 OI	F 3