
	<b>TECHNICAL DATA SHEET</b>	code	<b>URM76NH</b>
		version	<b>1</b>
		date	<b>2007-10-25</b>
	<b>COAX URM 76 FRNC</b>	page	<b>1/2</b>

## APPLICATION

Coaxial communication cable based on BS2316.

## CONSTRUCTION




1	Inner conductor	Stranded tinned copper
2	Dielectric	Solid PE
3	Braid	Bare copper
4	Sheath	FRNC according the European Standard HD 624.

## REQUIREMENTS AND TEST METHODS

Test methods in accordance with European standard EN 50289.

### Mechanical characteristics

1. Inner conductor:	7 x 0.32 mm
Diameter:	0.96 mm ± 0.02 mm
2. Dielectric:	
Diameter:	2.95 mm ± 0.15 mm
3. Outer conductor:	
Diameter screen:	3.63 mm ± 0.2 mm
Coverage braid:	91 % ± 4 %
4. Sheath:	
Diameter:	5.0 mm ± 0.25 mm
Tensile strength:	≥ 9 N/mm <sup>2</sup>
Elongation at break:	≥ 125 %
5. Cable:	
Crush resistance of cable:	< 1% (load of 700N)
Storage/operating temperature:	-15°C to +70°C
Minimum installation temperature:	-5 °C
Minimum static bend radius:	25 mm

	<b>TECHNICAL DATA SHEET</b>	code	<b>URM76NH</b>
		version	<b>1</b>
		date	<b>2007-10-25</b>
	<b>COAX URM 76 FRNC</b>	page	<b>2/2</b>

**Electrical characteristics**

Mean characteristic impedance:  $50 \pm 2 \Omega$   
 Regularity of impedance:  $> 40 \text{ dB}$   
 DC resistance inner conductor:  $\leq 31.8 \Omega/\text{km}$   
 Capacitance:  $98 \text{ pF/m} \pm 5 \text{ pF/m}$   
 Nominal velocity of propagation:  $66 \%$   
 Insulation resistance:  $> 2 \cdot 10^4 \text{ M}\Omega \cdot \text{km}$   
 Voltage Rating  
     DC: 4 kVdc  
     RMS: 2 kVrms

Return loss at      5-30 MHz:  $\geq 20 \text{ dB}^*$   
                           30-470 MHz:  $\geq 20 \text{ dB}^*$   
                           470-1000 MHz:  $\geq 18 \text{ dB}^*$

\*Max. 3 peak values 4 dB lower than specified.

**Nominal Attenuation:**

100 MHz: 15.5 dB/100m  
 200 MHz: 22.2 dB/100m  
 600 MHz: 39.8 dB/100m  
 1000 MHz: 52.7 dB/100m

**REVISIONS**

#	Description	Date	Initials



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.